

PTFE Thread Sealants & Specialty Chemicals

Blue Monster Stay-Soft Thread Sealant with PTFE

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly. Easy cleanup and has indefinite shelflife.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.



Brushable from -15°F (-20°C) to +400°F (204°C)
Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm²)
Liquids up to 10,000 PSI (703.1 kg/cm²)

Meets Mil. Spec. TT-S-1732

Blue Monster® Copper Anti-Seize Sealant

Copper anti-seize lubricant for use on all metal pipe and fittings.

Mill-Rose Blue Monster Copper Anti-Seize is a specially formulated copper-based thread sealant for high temperature up to 1800°F (982°C) and high pressure environments. Blue Monster Copper Anti-Seize lubricant will not bleed, separate, or settle. Prevents pressure leakage and seizing resulting from high temperature, freezing, heavy loads, corrosion, and vibration. Contains no grit. Prevents rust and corrosion.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76024	10 oz. / .625 lb. / 283 g	12/case	9.4 lbs.
76026	16 oz. / 1 lb. / 454 g	12/case	15.2 lbs.

- Copper anti-seize lubricant for use on all metal pipe and fittings.
- Temperature Range Use:
Gases: -0°F (-17°C) to 1800°F (982°C)
Liquids: -0°F (-17°C) to 1800°F (982°C)
Brushable to: 10°F (-12°C)
Pour Point: 32°F (0°C)

Blue Monster® Nickel Anti-Seize Sealant

Pure nickel anti-seize compound for use on stainless steel pipe and fittings.

Blue Monster Nickel Anti-Seize is an extreme service anti-seize lubricant and thread sealant for use in a high temperature environment (up to 2600°F /1427°C). For use in applications where copper, lead, moly-disulfide, chlorides, and fluorides cannot be tolerated. Blue Monster Nickel Anti-Seize lubricant is chemically inert and can be used with most chemicals that are unstable with copper-type compounds. Provides excellent resistance to chemical oxidation and/or corrosion. Prevents rusting, seizing, welding, or galling. Not for use on potable water systems. Not for use on potable water systems.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76020	1/2 pint / 8 fl. oz. / 237 ml	12	10 lbs.
76022	1 pint / 16 fl. oz. / 473 ml	12	19 lbs.

- High temperature lubricant and thread sealant for use on stainless steel, PVC, CPVC, nylon, polypropylene, plastics and all metals.
- Temperature Range Use:
Gases: -0°F (-17°C) to 2600°F (1427°C)
Liquids: -0°F (-17°C) to 2600°F (1427°C)
Brushable to: 10°F (-12°C)
Pour Point: 32°F (0°C)

All Purpose Lubricating Oil with Zoom Spout

The highest quality turbine lubricating oil! Ideal for use on industrial equipment, electric motors from 1/3HP to 5HP, shop tools, bearings, shafts and virtually all mechanical linkages. Available in a 4 ounce container with the patented Zoom Spout.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
70704	Lubricating Oil with Zoom Spout	12	4.0 lbs.