


Bushings, Nipples, Locknuts and Plugs

Meets and surpasses NEC® requirements!

Insulated Throat Fittings


- Steel or malleable iron (steel through 1½")
- Exceeds NEC 373-6C requirements for protection of ungrounded connectors at entrance to raceways, pull boxes and junctions
- Recognizable by distinctive trademarked blue insulating liner in throat
- Reduces wire pulling effort by as much as 50%
- Temperature rating of 105° C
- Look for the unique T&B blue color, ensuring the highest quality fitting



Locknut-type base improves bonding and resists loosening under vibration.

Metallic Bushings

- Aluminum, steel or malleable iron (steel through 1½")
- Smoothly rounded shoulder covers end of conduit
- Broad flange covers knockout hole
- High ribs for easy tightening with fingers or with wrench
- ½" to 1½" sizes, formed in steel, feature extra-smooth shoulders



CAT. NO.		DIMENSIONS (IN.)		
STL. OR M.I.	ALUM.	SIZE	A	B
1222	1222AL	½"	1½/32	29/64
1223	1223AL	¾"	1½/32	31/64
1224	1224AL	1"	119/32	11/32
1225	1225AL	1¼"	115/16	21/32
1226	1226AL	1½"	23/16	23/32
1227	1227AL	2"	211/16	1/8
1228	1228AL	2½"	33/16	1/32
1229	1229AL	3"	321/32	5/16
1230	1230AL	3½"	41/16	11/16
1231	1231AL	4"	47/8	13/32
1232†	1232AL†	4½"	—	—
586	586AL	5"	521/32	13/32
587	587AL	6"	73/16	113/32

† Not CSA Certified

Catalog series 1222 thru 1232, 586 and 587 are available in aluminum. Add suffix AL to Cat. No. The aluminum series fittings are not CSA certified.

CAT. NO.		DIMENSIONS (IN.)		
STL. OR M.I.	ALUM.	SIZE	A	B
122	122AL	½"	1½/32	13/32
123	123AL*	¾"	1¼	1/16
124	124AL**	1"	13/16	1/2
125-TB	125AL	1¼"	13/32	9/16
126	126AL	1½"	23/32	19/32
127	127AL	2"	23/32	5/8
128	128AL	2½"	33/16	3/4
129	129AL	3"	321/32	13/16
130-TB	130AL	3½"	43/8	15/16
131-TB	131AL	4"	415/16	1
132-TB	—	4½"	51/16	13/64
133-TB	133AL	5"	6	13/16
134-TB	134AL	6"	7¼	1¼

* Not UL Listed or CSA Certified

UL File No. E-23018


** Not CSA Certified

CSA File No. 2884

Available with DURA-PLATE® Finish.

Perfect threads for easy thread-on!

Plastic Insulating Bushings



- Impact-resistant plastic insulation
- Ribbed for easy, secure gripping
- UL Listed 105° C



CAT. NO.	SIZE	DIMENSIONS (IN.)	
		A	B
222-TB	½"	11/16	3/8
223-TB	¾"	13/32	13/32
224	1"	13/16	9/16
225-TB	1¼"	129/32	9/16
226	1½"	21/32	9/16
227	2"	225/32	5/8
228-TB	2½"	33/8	3/4
229-TB	3"	41/16	3/4
230-TB	3½"	47/8	7/8
231	4"	51/8	1
232	4½"	511/16	1
233	5"	63/16	1
234	6"	77/16	1

UL Rated flame retardant 94V-1