

Liquidtight Flexible Metal Conduit Fittings
T&B Catalog Number:

5232GRX

UPC Number:

78621074168

Status:

Active

Description:

1/2 Inch steel external bonding liquidtight connector with lay-in-lug, non-insulated

Features

Ability to install quickly with low torque effort

Application

To positively bond conduit to box or enclosure

General

| | |
|---------------------|--------------------------------------|
| Trade Size (inches) | 1/2 |
| Material | Steel |
| Finish | Electro Zinc Plated/Chromate Coating |
| Ground Wire | 14-8 |

Dimension Information

| | |
|----------------------|--------|
| Dimension A (inches) | 1 3/8 |
| Dimension B (inches) | 1 9/16 |
| Dimension C (inches) | 9/16 |

Packaging

| | |
|--------------------|-----------------|
| T&B Inner Pack | 25 |
| Package in Units | 100 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 19 lbs. per 100 |

Certifications

| | |
|-----------------|----|
| RoHS Compliance | No |
|-----------------|----|

Certifications

File Nbr:

E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com