

**Liquidtight Flexible Metal Conduit Fittings****T&B Catalog Number:**

5332GR

**UPC Number:**

78621089998

**Status:**

Active

**Description:**

1/2 Inch External Bonding Liquidtight, Flexible Metal Conduit, Straight, Insulated, With Revolver Lug, With Tin Plated Cu Alloy Lug for #14 to #4 Ground Wire, for Use In Wet Locations, 25 Pieces

**Features**

Ability to install quickly with low torque effort

**Application**

To positively bond conduit to box or enclosure

**General**

Trade Size (inches)	1/2
Material	Steel
Finish	Electro Zinc Plated/Chromate Coating
Ground Wire	14-8

**Dimension Information**

Dimension A (inches)	1 3/8
Dimension B (inches)	1 9/16
Dimension C (inches)	9/16

**Specifications**

3dmodel	Available on Website
---------	----------------------

**Packaging**

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	19.81 lbs. per 100

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**Certifications**

File Nbr:

E 3060

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com