



## Liquidtight Flexible Metal Conduit Fittings

**T&B Catalog Number:**

5356GR

**UPC Number:**

78621089635

**Status:**

Active

**Description:**

1-1/2 Inch 90 Degree Malleable Iron External Bonding Liquidtight Insulated Connector

### Features

Ability to install quickly with low torque effort

### Application

To positively bond conduit to box or enclosure

### General

|                     |                                      |
|---------------------|--------------------------------------|
| Trade Size (inches) | 1 1/2                                |
| Material            | Malleable Iron                       |
| Finish              | Electro Zinc Plated/Chromate Coating |
| Ground Wire         | 4-2/0                                |

### Dimension Information

|                      |         |
|----------------------|---------|
| Dimension A (inches) | 3 1/4   |
| Dimension B (inches) | 2 15/16 |
| Dimension C (inches) | 13/16   |

### Specifications

|         |                      |
|---------|----------------------|
| 3dmodel | Available on Website |
|---------|----------------------|

### Packaging

|                    |                  |
|--------------------|------------------|
| T&B Inner Pack     | 2                |
| Package in Units   | 10               |
| T&B Sold in UOM    | Each             |
| T&B Weight Per UOM | 200 lbs. per 100 |

### Certifications

|                 |    |
|-----------------|----|
| RoHS Compliance | No |
|-----------------|----|

### Certifications



File Nbr:

E 3060

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com