

Type B Liquidtight Tubing & Fittings

T&B Catalog Number:

UPC Number:
Status:
Description:

EFC100
 78621078963
 Active



1 Inch black corrugated PVC flexible tubing.

Features

- Maximum flexibility in tight applications.
- Extremely fast installation
- Liquidtight with specified fittings.
- Good tensile strength provides excellent pullout protection and smooth inner diameter allows easy wire pulling.

Application

Protection of fiber optic cable, installation of instrumentation and control cable, indoor and outdoor lighting, packaging equipment, marine and ship-board wiring, and flexing-component wiring protection on robots, graphic arts equipments, etc.

General

Material	PVC
Color	Black
Working Temperatures	-18 C to +60 C

Dimension Information

Size (inches)	1
I.D. - Minimum (inches)	1.041
I.D. - Maximum (inches)	1.066
O.D. - Minimum (inches)	1.29
O.D. - Maximum (inches)	1.315

Packaging

T&B Order Multiple	100
Package in Units	100
T&B Sold in UOM	Feet
T&B Weight Per UOM	19.81 lbs. per 100

Application Support

Guide to Nonmetallic Conduit Applications	Available on Website
XTRAFLEX System Specifications	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
 E 96548

For further technical assistance, please contact us...

Memphis, TN 38125
www.tnb.com

8155 T&B Blvd.
Memphis, TN 38125

Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com