

**Type B Liquidtight Tubing & Fittings****T&B Catalog Number:**

LTC200

**UPC Number:**

78621078959

**Status:**

Active

**Description:**

2 Inch black non-metallic Type B industrial grade liquidtight conduit.

**Features**

Fast installation, even in tight or cramped spaces.  
 Smooth inner diameter allows easy wire pulling.  
 Smooth outer jacket uses material approved for outdoor use, is sunlight resistant and oil resistant.  
 Lightweight and liquidtight.

**Application**

Machine tools, motor hookups, food processing equipment, extensions from wire ways, and sensor and micro switch wiring found in control consoles.

**General**

Material	PVC
Color	Black
Working Temperatures	-18 C to +105 C

**Dimension Information**

Size (inches)	2
I.D. - Minimum (inches)	2.02
I.D. - Maximum (inches)	2.045
O.D. - Minimum (inches)	2.34
O.D. - Maximum (inches)	2.375

**Packaging**

T&B Order Multiple	50
Package in Units	50
T&B Sold in UOM	Feet
T&B Weight Per UOM	74.31 lbs. per 100

**Application Support**

Guide to Nonmetallic Conduit Applications	Available on Website
XTRAFLEX System Specifications	Available on Website

**Certifications**

RoHS Compliance	Yes
-----------------	-----

**Certifications**

File Nbr:  
E 95745

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com