



**Rigid/IMC Conduit Fittings-Hazardous Location
T&B Catalog Number:**

UPC Number: PLG2-TB
78621005749
Status: Active
Description:

Recessed Plugs, Gray Iron, Threads (NPT) 3/4 in.; with flush head for hazardous and non-hazardous locations.

Application

To close threaded conduit hubs.

General

Material Gray Iron

Dimension Information

Threads (NPT) (inches) 3/4

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 10
Package in Units 50
T&B Sold in UOM Each
T&B Weight Per UOM 11.19 lbs. per 100

Notes

Class I, Div. 1 & 2, Groups A, B, C, D - Explosion-proof
Class II, Div. 1, Groups E, F, G - Dust-Ignitionproof
Class III, Div. 1&2 - Raintight

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 193396

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com