



**Rigid/IMC Conduit Fittings-Hazardous Location
T&B Catalog Number:**

UPC Number: RE21-TB
Status: 78621005865
Description: Active

3/4 in.-1/2 in. Reducing Bushing, Steel-Zinc Plated.

Features

All Hubs have NPT threads with a minimum of five full threads and integral bushing for preventing damage to wires.

Application

Reduces conduit hubs to a smaller size.

General

Material: Steel
Finish: Zinc Plated

Dimension Information

A Male (NPT) (inches): 3/4
B Female (NPT) (inches): 1/2

Specifications

3dmodel: Available on Website

Packaging

T&B Inner Pack: 50
Package in Units: 100
T&B Sold in UOM: Each
T&B Weight Per UOM: 6.75 lbs. per 100

Notes

Class I, Div. 1 & 2, Groups A, B, C, D - Explosion-proof
 Class II, Div. 1, Groups E, F, G - Dust-Ignitionproof
 Class III, Div. 1&2 - Raintight

Certifications

RoHS Compliance: Yes

Certifications



File Nbr:
 E 193396

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
 www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com