



Rigid/IMC Conduit Fittings-Hazardous Location T&B Catalog Number:

UPC Number: RE63-TB
78621006969
Status: Active
Description:

2 in.-1 in. Reducing Bushing, Steel-Zinc Plated.

Features

All Hubs have NPT threads with a minimum of five full threads and integral bushing for preventing damage to wires.

Application

Reduces conduit hubs to a smaller size.

General

Material Steel
Finish Zinc Plated

Dimension Information

A Male (NPT) (inches) 2
B Female (NPT) (inches) 1

Specifications

3dmodel Available on Website

Packaging

T&B Order Multiple 5
T&B Inner Pack 5
Package in Units 25
T&B Sold in UOM Each
T&B Weight Per UOM 85.5 lbs. per 100

Notes

Class I, Div. 1 & 2, Groups A, B, C, D - Explosion-proof

Class II, Div. 1, Groups E, F, G - Dust-Ignitionproof

Class III, Div. 1&2 - Raintight

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 193396

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com