

MINITERMS
Female Disconnects
F SERIES

FEATURES

VINYL:

Electro tin plated copper, 600V, 105 °C. Female, quick disconnect, Vinyl



UN-INSULATED-BARE:

Electro tin plated copper, 600V, 105 °C. Female quick disconnect



NYLON:

Turned up edges give this disconnect more safety and reliability. 600V, 105 °C, Nylon



| STYLE | INSULATION TYPE | WIRE RANGE | STUD SIZE | CERTIFICATION VARIANCE |
|--------|-----------------|------------|-----------|------------------------|
| Female | Vinyl | 22-18 | 0.110 | |
| Female | Vinyl | 22-18 | 0.110 | UL |
| Female | Vinyl | 22-18 | 0.187 | |
| Female | Vinyl | 22-18 | 0.187 | UL |
| Female | Vinyl | 22-18 | 0.250 | |
| Female | Vinyl | 16-14 | 0.110 | UL |
| Female | Vinyl | 16-14 | 0.110 | UL |
| Female | Vinyl | 16-14 | 0.187 | |
| Female | Vinyl | 16-14 | 0.187 | |
| Female | Vinyl | 16-14 | 0.250 | |
| Female | Vinyl | 12-10 | 0.250 | |
| Female | Un-insulated | 22-18 | 0.110 | UL |
| Female | Un-insulated | 22-18 | 0.110 | UL |
| Female | Un-insulated | 22-18 | 0.187 | UL |
| Female | Un-insulated | 22-18 | 0.187 | UL |
| Female | Un-insulated | 22-18 | 0.250 | |
| Female | Un-insulated | 16-14 | 0.110 | UL |
| Female | Un-insulated | 16-14 | 0.110 | |
| Female | Un-insulated | 16-14 | 0.187 | UL |
| Female | Un-insulated | 16-14 | 0.187 | UL |
| Female | Un-insulated | 16-14 | 0.250 | |
| Female | Un-insulated | 12-10 | 0.250 | |
| Female | Un-insulated | 8 | 0.250 | NON-UL |
| Female | Nylon | 22-18 | 0.110 | NON-UL |
| Female | Nylon | 22-18 | 0.110 | UL |
| Female | Nylon | 22-18 | 0.187 | UL |
| Female | Nylon | 22-18 | 0.187 | UL |
| Female | Nylon | 22-18 | 0.250 | |
| Female | Nylon | 16-14 | 0.110 | UL |
| Female | Nylon | 16-14 | 0.110 | UL |
| Female | Nylon | 16-14 | 0.187 | UL |
| Female | Nylon | 16-14 | 0.187 | |
| Female | Nylon | 16-14 | 0.250 | |
| Female | Nylon | 12-10 | 0.250 | |

"S" PACKS

PRO PACKS

STD PACKS

BULK PACKS

| L (IN) | W (IN) | CAT. NO. | QTY | CAT. NO. | QTY | CAT. NO. | QTY | CAT. NO. | QTY |
|--------|--------|---------------------|-----|---------------------|-----|-------------------|-----|------------------------|------|
| 0.728 | 0.125 | - | - | - | - | F22-110-2V | 100 | F22-110-2V-BULK | 1000 |
| 0.789 | 0.170 | - | - | - | - | F22-110-3V | 100 | F22-110-3V-BULK | 1000 |
| 0.748 | 0.196 | - | - | - | - | F22-187-2V | 100 | F22-187-2V-BULK | 1000 |
| 0.789 | 0.250 | - | - | - | - | F22-187-3V | 100 | F22-187-3V-BULK | 1000 |
| 0.826 | 0.259 | F22-250-3V-S | 25 | F22-250-3V-P | 80 | F22-250-3V | 100 | F22-250-3V-BULK | 1000 |
| 0.789 | 0.170 | - | - | - | - | F16-110-2V | 100 | F16-110-2V-BULK | 1000 |
| 0.789 | 0.170 | - | - | - | - | F16-110-3V | 100 | F16-110-3V-BULK | 1000 |
| 0.748 | 0.196 | F16-187-2V-S | 25 | - | - | F16-187-2V | 100 | F16-187-2V-BULK | 1000 |
| 0.748 | 0.196 | - | - | - | - | F16-187-3V | 100 | F16-187-3V-BULK | 1000 |
| 0.826 | 0.259 | F16-250-3V-S | 25 | F16-250-3V-P | 70 | F16-250-3V | 100 | F16-250-3V-BULK | 1000 |
| 0.925 | 0.259 | F12-250-3V-S | - | F12-250-3V-P | 50 | F12-250-3V | 50 | F12-250-3V-BULK | 500 |
| 0.550 | 0.150 | - | - | - | - | F22-110-2 | 100 | F22-110-2-BULK | 1000 |
| 0.554 | 0.150 | - | - | - | - | F22-110-3 | 100 | F22-110-3-BULK | 1000 |
| 0.565 | 0.233 | - | - | - | - | F22-187-2 | 100 | F22-187-2-BULK | 1000 |
| 0.565 | 0.233 | - | - | - | - | F22-187-3 | 100 | F22-187-3-BULK | 1000 |
| 0.629 | 0.259 | - | - | F22-250-3-P | 100 | F22-250-3 | 100 | F22-250-3-BULK | 1000 |
| 0.557 | 0.149 | - | - | - | - | F16-110-2 | 100 | F16-110-2-BULK | 1000 |
| 0.531 | 0.125 | - | - | - | - | F16-110-3 | 100 | F16-110-3-BULK | 1000 |
| 0.556 | 0.233 | - | - | - | - | F16-187-2 | 100 | F16-187-2-BULK | 1000 |
| 0.559 | 0.233 | - | - | - | - | F16-187-3 | 100 | F16-187-3-BULK | 1000 |
| 0.629 | 0.259 | - | - | F16-250-3-P | 125 | F16-250-3 | 100 | F16-250-3-BULK | 1000 |
| 0.669 | 0.259 | - | - | - | - | F12-250-3 | 50 | F12-250-3-BULK | 500 |
| 0.665 | 0.320 | - | - | - | - | F8-250-3 | 50 | F8-250-3-BULK | 1000 |
| 0.789 | 0.163 | - | - | - | - | F22-110-2N | 100 | F22-110-2N-BULK | 1000 |
| 0.789 | 0.210 | - | - | - | - | F22-110-3N | 100 | F22-110-3N-BULK | 1000 |
| 0.789 | 0.125 | - | - | - | - | F22-187-2N | 100 | F22-187-2N-BULK | 1000 |
| 0.789 | 0.125 | - | - | - | - | F22-187-3N | 100 | F22-187-3N-BULK | 1000 |
| 0.866 | 0.259 | - | - | - | - | F22-250-3N | 100 | F22-250-3N-BULK | 1000 |
| 0.789 | 0.163 | - | - | - | - | F16-110-2N | 100 | F16-110-2N-BULK | 1000 |
| 0.789 | 0.163 | - | - | - | - | F16-110-3N | 100 | F16-110-3N-BULK | 1000 |
| 0.789 | 0.238 | - | - | - | - | F16-187-2N | 100 | F16-187-2N-BULK | 1000 |
| 0.787 | 0.196 | - | - | - | - | F16-187-3N | 100 | F16-187-3N-BULK | 1000 |
| 0.866 | 0.259 | - | - | - | - | F16-250-3N | 100 | F16-250-3N-BULK | 1000 |
| 0.944 | 0.259 | - | - | - | - | F12-250-3N | 50 | F12-250-3N-BULK | 500 |