

**MINITERMS**  
**Female Disconnects**  
**F SERIES**

**FEATURES**

**VINYL:**

Electro tin plated copper, 600V, 105°C. Female, quick disconnect, Vinyl



**UN-INSULATED-BARE:**

Electro tin plated copper, 600V, 105°C. Female quick disconnect



**NYLON:**

Turned up edges give this disconnect more safety and reliability. 600V, 105°C, Nylon



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Female	Vinyl	22-18	0.110	
Female	Vinyl	22-18	0.110	UL
Female	Vinyl	22-18	0.187	
Female	Vinyl	22-18	0.187	UL
Female	Vinyl	22-18	0.250	
Female	Vinyl	16-14	0.110	UL
Female	Vinyl	16-14	0.110	UL
Female	Vinyl	16-14	0.187	
Female	Vinyl	16-14	0.187	
Female	Vinyl	16-14	0.250	
Female	Vinyl	12-10	0.250	
Female	Un-insulated	22-18	0.110	UL
Female	Un-insulated	22-18	0.110	UL
Female	Un-insulated	22-18	0.187	UL
Female	Un-insulated	22-18	0.187	UL
Female	Un-insulated	22-18	0.250	
Female	Un-insulated	16-14	0.110	UL
Female	Un-insulated	16-14	0.110	
Female	Un-insulated	16-14	0.187	UL
Female	Un-insulated	16-14	0.187	UL
Female	Un-insulated	16-14	0.250	
Female	Un-insulated	12-10	0.250	
Female	Un-insulated	8	0.250	NON-UL
Female	Nylon	22-18	0.110	NON-UL
Female	Nylon	22-18	0.110	UL
Female	Nylon	22-18	0.187	UL
Female	Nylon	22-18	0.187	UL
Female	Nylon	22-18	0.250	
Female	Nylon	16-14	0.110	UL
Female	Nylon	16-14	0.110	UL
Female	Nylon	16-14	0.187	UL
Female	Nylon	16-14	0.187	
Female	Nylon	16-14	0.250	
Female	Nylon	12-10	0.250	

## "S" PACKS

## PRO PACKS

## STD PACKS

## BULK PACKS

L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.728	0.125	-	-	-	-	<b>F22-110-2V</b>	100	<b>F22-110-2V-BULK</b>	1000
0.789	0.170	-	-	-	-	<b>F22-110-3V</b>	100	<b>F22-110-3V-BULK</b>	1000
0.748	0.196	-	-	-	-	<b>F22-187-2V</b>	100	<b>F22-187-2V-BULK</b>	1000
0.789	0.250	-	-	-	-	<b>F22-187-3V</b>	100	<b>F22-187-3V-BULK</b>	1000
0.826	0.259	<b>F22-250-3V-S</b>	25	<b>F22-250-3V-P</b>	80	<b>F22-250-3V</b>	100	<b>F22-250-3V-BULK</b>	1000
0.789	0.170	-	-	-	-	<b>F16-110-2V</b>	100	<b>F16-110-2V-BULK</b>	1000
0.789	0.170	-	-	-	-	<b>F16-110-3V</b>	100	<b>F16-110-3V-BULK</b>	1000
0.748	0.196	<b>F16-187-2V-S</b>	25	-	-	<b>F16-187-2V</b>	100	<b>F16-187-2V-BULK</b>	1000
0.748	0.196	-	-	-	-	<b>F16-187-3V</b>	100	<b>F16-187-3V-BULK</b>	1000
0.826	0.259	<b>F16-250-3V-S</b>	25	<b>F16-250-3V-P</b>	70	<b>F16-250-3V</b>	100	<b>F16-250-3V-BULK</b>	1000
0.925	0.259	<b>F12-250-3V-S</b>	-	<b>F12-250-3V-P</b>	50	<b>F12-250-3V</b>	50	<b>F12-250-3V-BULK</b>	500
0.550	0.150	-	-	-	-	<b>F22-110-2</b>	100	<b>F22-110-2-BULK</b>	1000
0.554	0.150	-	-	-	-	<b>F22-110-3</b>	100	<b>F22-110-3-BULK</b>	1000
0.565	0.233	-	-	-	-	<b>F22-187-2</b>	100	<b>F22-187-2-BULK</b>	1000
0.565	0.233	-	-	-	-	<b>F22-187-3</b>	100	<b>F22-187-3-BULK</b>	1000
0.629	0.259	-	-	<b>F22-250-3-P</b>	100	<b>F22-250-3</b>	100	<b>F22-250-3-BULK</b>	1000
0.557	0.149	-	-	-	-	<b>F16-110-2</b>	100	<b>F16-110-2-BULK</b>	1000
0.531	0.125	-	-	-	-	<b>F16-110-3</b>	100	<b>F16-110-3-BULK</b>	1000
0.556	0.233	-	-	-	-	<b>F16-187-2</b>	100	<b>F16-187-2-BULK</b>	1000
0.559	0.233	-	-	-	-	<b>F16-187-3</b>	100	<b>F16-187-3-BULK</b>	1000
0.629	0.259	-	-	<b>F16-250-3-P</b>	125	<b>F16-250-3</b>	100	<b>F16-250-3-BULK</b>	1000
0.669	0.259	-	-	-	-	<b>F12-250-3</b>	50	<b>F12-250-3-BULK</b>	500
0.665	0.320	-	-	-	-	<b>F8-250-3</b>	50	<b>F8-250-3-BULK</b>	1000
0.789	0.163	-	-	-	-	<b>F22-110-2N</b>	100	<b>F22-110-2N-BULK</b>	1000
0.789	0.210	-	-	-	-	<b>F22-110-3N</b>	100	<b>F22-110-3N-BULK</b>	1000
0.789	0.125	-	-	-	-	<b>F22-187-2N</b>	100	<b>F22-187-2N-BULK</b>	1000
0.789	0.125	-	-	-	-	<b>F22-187-3N</b>	100	<b>F22-187-3N-BULK</b>	1000
0.866	0.259	-	-	-	-	<b>F22-250-3N</b>	100	<b>F22-250-3N-BULK</b>	1000
0.789	0.163	-	-	-	-	<b>F16-110-2N</b>	100	<b>F16-110-2N-BULK</b>	1000
0.789	0.163	-	-	-	-	<b>F16-110-3N</b>	100	<b>F16-110-3N-BULK</b>	1000
0.789	0.238	-	-	-	-	<b>F16-187-2N</b>	100	<b>F16-187-2N-BULK</b>	1000
0.787	0.196	-	-	-	-	<b>F16-187-3N</b>	100	<b>F16-187-3N-BULK</b>	1000
0.866	0.259	-	-	-	-	<b>F16-250-3N</b>	100	<b>F16-250-3N-BULK</b>	1000
0.944	0.259	-	-	-	-	<b>F12-250-3N</b>	50	<b>F12-250-3N-BULK</b>	500