

Product data sheet

Characteristics

QU816D400SL

Meter mains, QO, combination service entrance, ringless socket, 400A, surface mount, maximum 8 spaces, 16 circuits, class 320 lever bypass



Main

| | |
|---------------------------|-------------|
| Product or component type | Meter Mains |
| Range of product | QO |

Complementary

| | |
|---------------------------|---|
| Line Rated Current | 400 A |
| Short-circuit current | 25 kA |
| Network number of phases | 1 |
| Meter socket type | Ringless |
| Mounting | Surface |
| Number of spaces | 8 |
| Number of circuits | 16 |
| Number of Tandem Breakers | 8 |
| Hub type | A-L |
| Electrical connection | Studs line side Feed-thru lugs service ground |
| Wire Size | AWG 4...250 kcmil aluminium)service ground AWG 4...250 kcmil copper)service ground |
| Disconnect | Service disconnect (factory installed) |
| Main Breaker Rating | 200 A |
| Branch Breaker Rating | 200 A |
| Service feed location | UG |
| Bypass type | Class 320 lever bypass |
| Maximum Depth | 7.87 in (199.90 mm) |
| Width | 28.25 in (717.55 mm) |
| Height | 43.00 in (1092.20 mm) |

Environment

| | |
|------------------------|-----------|
| Product certifications | UL E-6294 |
|------------------------|-----------|

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 00022 - QO METER MAINS |
| Discount Schedule | DE3A |
| GTIN | 00785901468455 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 115 lb(US) (52.16 kg) |

| | |
|-------------------|-----|
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------|-------------------|
| Package 1 Height | 0.80 ft (0.244 m) |
| Package 1 width | 2.44 ft (0.744 m) |
| Package 1 Length | 3.51 ft (1.069 m) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|