

# SUBMITTAL SHEET

## 800 Small Diameter Series

APOLLOXPRESS® Press End Copper Coupling  
Cx C with Stop (½" through 2")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



### DESCRIPTION

The APOLLOXPRESS® 800 Small Diameter Press Coupling features a Lead-Free dezincification resistant copper body and an EPDM O-Ring. Our Small Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

### FEATURES

- Lead-Free Construction
- Leak-Before-Press Technology
- Compatible with Pro-Press™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

### PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: 0°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

### APPROVALS

- NSF/ANSI NSF 61 – Water Quality
- NSF/ANSI NSF-372 – Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

### APOLLOXPRESS

- Small Diameter Sizes ½", ¾", 1", 1 ¼", 1 ½" & 2"
- Model 800, Coupling with Stop C x C

### STANDARD MATERIALS

Part Name	Material
Body	UNS C12200 Copper
O-Ring	EPDM
Lubrication	Silicone, ANSI/NSF-61 Listed

### DIMENSIONS

Item No.	Description	Dimension (in.)								(lb.)
		A	B	C*	D**	E*	Height	Width	Depth	
10075500	800 ½ CxC	1.72	0.95	0.81	0.11	0.81	0.95	1.72	0.95	0.08
10075502	800 ¾ CxC	1.89	1.24	0.88	0.12	0.88	1.24	1.89	1.24	0.13
10075504	800 1 CxC	2.06	1.49	0.92	0.23	0.92	1.49	2.06	1.49	0.19
10075506	800 1¼ CxC	2.34	1.75	1.04	0.25	1.04	1.75	2.34	1.75	0.25
10075508	800 1½ CxC	3.10	2.09	1.43	0.24	1.43	2.09	3.10	2.09	0.50
10075510	800 2 CxC	3.42	2.56	1.59	0.25	1.59	2.56	3.42	2.56	0.62

\* Tolerance +/- .045"

\*\* Tolerance +.09 / -.03

### Elkhart Products Corporation

1255 Oak Street, Elkhart, IN 46514

www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.

