

8000



Specifications

Description: Bolt-in and snap-in mounting for 1/4" x 1 1/4" fuses.

Construction: Blocks are molded flame retardant thermoplastic. Clips are bright tin-plated, spring-bronze.

Ratings:

Volts: — 300V

Amps: — 25A (See catalog numbers table)

Agency information: CE, UL Recognized ; File E14853, Guide IZLT2, CSA Certified Class 6225-01, File 47235.

Anti-rotation pin: Single-pole blocks may be ordered without the anti-rotational pin simply by adding an "X" to the number of poles (Example: BK/S-8000-1X).

Carton quantity: 10; shelf package: 100.

Bulk carton: Single-pole and 2-pole fuse blocks — 1,000; Multiple-pole fuse blocks — 3- to 8-pole: 200; 9- to 12-pole: 50. When ordering bulk quantities, prefix "BK/" to catalog number: (Example: BK/S-8001-1-SNP).

Catalog numbers

Bolt-in mounting

Basic catalog numbers	Series	Terminal	Angle	Agency maximums	Poles (suffix)
S-8001-	8000	Solder	0°	UL 30A	1 - 12
S-8002-			40°	CSA 21A	
S-8101-	8100	3/16" Quick connect	0°	UL 20A	
S-8102-			40°	CSA 13A	
S-8201-	8200	1/4" Quick connect side	0°	UL 30A	
S-8202-			40°	CSA 16A	
S-8203-			—	—	
S-8301-	8300	Screw	—	UL 30A CSA 25A	

Snap-in mounting

Catalog numbers	Series	Terminal	Angle	Agency maximums	Poles (suffix)
S-8001-1-SNP	8000	Solder	0°	UL 25A	Available only in single pole
S-8002-1-SNP			40°	CSA 21A	
S-8101-1-SNP	8100	3/16" Quick connect	0°	UL 20A	
S-8102-1-SNP			40°	CSA 13A	
S-8201-1-SNP	8200	1/4" Quick connect	0°	UL 20A	
S-8203-1-SNP			Side	CSA 16A	

Catalog number build-a-code



Catalog Code

BK/ S-8 0 00 -00

Prefix for Bulk Packing
Series 8000—
Product Line
Type Terminal
"0" - Solder
"1" - 3/16" Quick Connect
"2" - 1/4" Quick Connect
"3" - Screw
Terminal Angle
"01" - straight (0.)
"02" - 40
"03" - side
Number of Poles (1-12)
*Available only in single pole

Data Sheet: 2101

Single-pole fuse blocks

Specifications

Description: Single-pole fuse block for 1/4" x 1 1/4" (6.4 x 31.8mm) size fuses.

Dimensions: See dimensions illustrations.

Construction: Bakelite base width 1/2" (12.7mm); spring-bronze, bright tin-lead plate clips.

Ratings:


Volts: — 250V

Amps: — 30A



4405 - 0° solder terminals with integral terminal and clip

Dimensions - in (mm)




4406 - Side solder terminal



4574 - Spare fuse block

Dimensions - in (mm)




2499 - Side quick-connect

Agency information: UL Recognized, Guide IZLT2, File E14853

Terminals: 1/4" (6.4mm); 15A, 250V

Dimensions - in (mm)



Note: Mounting screw hole diameter is 0.147" (3.7mm). Counterbore diameter, 0.636" (8.0mm). Max mounting screw no. 6.