

Pipe/Tube Cutting & Preparation

X-CEL™ Means Speed

Many of our most popular tubing cutters now include several X-CEL features to make your job quicker and easier.

- X-CEL Knob – cut tubing more quickly and easily with our larger, more ergonomic designs.
- X-CEL Wheel Pin – change your cutter wheel quickly using our new ball detent design...no tool needed...no lost clips!
- Spare cutter wheels included for maximum uptime.



Constant Swing Cutters with New X-CEL Features

- Telescoping feed screw design keeps the cutter at the same length regardless of tubing diameter – good for tight spaces.
- Features an enclosed feed screw to eliminate clogging and jamming, grooved rollers for close-to-flare cuts, and a fold-away reamer.
- Now includes X-CEL knob and X-CEL Pin for quicker cutting and wheel replacement.
- Made from high-strength zinc alloy.
- Spare cutter wheel included in the knob.
- Cuts copper, brass, and aluminum tubing and thin-wall conduit.

Catalog No.	Model No.	Description	Std. Wheel	Capacity		Weight		Standard Pack
				in.	mm	lb.	kg	
31622	150	Feed Cutter	E-3469	1/8-1 1/2	3-28	7/8	0.4	6
31627	150	Above w/H-D Wheel(s)	E-4546	1/8-1 1/2	3-28	7/8	0.4	6
66737	150-L	Constant Swing Cutter	E-3469	1/4-1 3/8	3-35	7/8	0.4	6
66742	150-LS	Above w/H-D Wheel(s)	E-4546	1/4-1 3/8	3-35	7/8	0.4	6



Enclosed Feed Cutters

- Cuts copper, brass and aluminum tubing and thin-wall conduit.
- Both Enclosed Feed Cutters have a quick-acting mechanism for faster size adjustments.
- Spare cutter wheel.

Catalog No.	Model No.	Description	Std. Wheel	Capacity		Weight		Standard Pack
				in.	mm	lb.	kg	
33055	205	Ratcheting Encl. Feed Cutter	E-3469	1/4-2 3/8	6-60	1 3/4	0.8	1
33070	205	Above w/H-D Wheel(s)	E-4546	1/4-2 3/8	6-60	1 3/4	0.8	1