



GigaSPEED X10D® XL® M4800 1U Modular Panel, 48 port, for SYSTIMAX Category 6A and 6 Information Outlets and Uniprise Category 6A Information Outlets

- Available for use with the DYMO® labeling solution

Product Classification

Portfolio	CommScope®
Brand	GigaSPEED X10D®
Product Type	RJ45 patch panel
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Dimensions

Depth	53.85 mm 2.12 in
Height	44.45 mm 1.75 in
Width	482.60 mm 19.00 in

Electrical Specifications

ANSI/TIA Category	6 6A
--------------------------	--------

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Intelligence Type	Passive
Color	Black
Package Quantity	1
Rack Type	EIA 19 in
Rack Units	1.0

Mechanical Specifications

Material Type	High-impact, flame retardant, thermoplastic Steel
----------------------	---

Regulatory Compliance/Certifications

Agency	Classification
---------------	-----------------------

RoHS 2011/65/EU
ISO 9001:2015

Compliant
Designed, manufactured and/or distributed under this quality management system

