



Uniprise Modular Jack, RJ45, category 6, T568A/T568B, unshielded, without dust cover, black

Product Classification

Portfolio	Uniprise®
Product Series	UNJ Series
Product Type	Modular jack
Regional Availability	North America

Dimensions

Compatible Insulated Conductor Diameter, maximum	1.450 mm 0.057 in
--	---------------------

Electrical Specifications

ANSI/TIA Category	6
Transmission Standard	ANSI/TIA-568-C.2 ISO/IEC 11801 Class E

Environmental Specifications

Flammability Rating	UL 94 V-0
---------------------	-----------

General Specifications

Cable Type	Unshielded
Color	Black
Mount Type	M Series faceplates and panels
Package Quantity	1
Packaging Type	Bag
Panel Thickness, recommended	1.60 mm

Mechanical Specifications

Conductor Gauge, solid	24–22 AWG
Conductor Gauge, stranded	26–24 AWG
Conductor Type	Solid Stranded
Contact Base Material	Beryllium copper

Contact Plating Material	Gold
Contact Plating Thickness	1.27 µm
Outlet Feature	Inverted jack face
Outlet Type	Standard
Termination Tool	SL Termination tool
Termination Type	IDC
Wiring	T568A T568B

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

