

HUBBELL
Wiring Device-Kellems

**Industrial Grade, Variable
Frequency Drive, Disconnect
Switches, Unfused Switch, Three
Pole, 60A 600V AC, Screw
Terminals, NEMA 4X Enclosure**

By Hubbell Wiring Device-Kellems
Catalog # [HBLDS6VFD](#)

Switches and Lighting Controls, Industrial Grade, Variable
Frequency Drive, Disconnect Switches, Unfused Switch, Three
Pole, 60A 600V AC, Screw Terminals, Gray, NEMA 4X Enclosure



General

Application	Labelless
Catalog Number	HBLDS6VFD
EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Type 4X, IP69k
Mounting Method	External fully adjustable feet
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	Electrical - Current Interrupting - Certified for current interrupting at full rated current & voltage Electrical - Dielectric Voltage - Withstands 3000V AC minimum Electrical - Max. Working Voltage - 600V AC RMS Environmental - Flammability - UL94-5VA and V0 Classification Environmental - Operating Temperature - Max Continuous 75°C, Min Continuous -40°C w/o impact Environmental - UV Resistance - All materials are UV stabilized Mechanical - Impact Resistance - In accordance with UL 746C Mechanical - Mounting - Non-Metallic - External fully adjustable feet Mechanical - Product Identification - Identification and ratings are part of external label Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions
Series	Non-Fused
Style	Heavy Duty
Type	Disconnect Switches
UPC	783585372716

Dimensions

Dimensions	11 in x 7.75 in x 5.94 in
Height	5.94 in
Length	11 in
Width	7.75 in

Electrical Ratings

Amperage Rating	60 A
Current / Amperage Rating	60 A
Current Rating	60 A
Dielectric Strength	Withstands 3000V AC minimum

Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

Logistics

Carton Quantity	1
Pallet Quantity	140

Product Assets

[Catalogs - WDK Catalog Full 2024](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK_MX-HBLDS6VFD-SPEC-EN | REV 6/2024