

## Straight Blade Devices, Explosion Proof, Male Plug, 15A 125V, 5-15P, Single Pack

By Hubbell Wiring Device-Kellems

Catalog # [UGP15231](#)



Straight Blade Devices, Explosion Proof, Male Plug, 15A 125V, 5-15P, Single Pack

### General

Color	Metallic
EU RoHS Indicator	Contact Manufacturer
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Performance	Electrical - Current Interrupting - Certified for current interrupting at full rated current
	Electrical - Dielectric Voltage - Withstands 2,000V minimum
	Environmental - Flammability - UL 94 HB or better
	Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
	Mechanical - Product Identification - Ratings are a permanent part of the device
	Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
	Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA
UPC	783585412351

### Dimensions

Dimensions	2.55 in x 1.69 in x 1.69 in
Height	1.69 in
Length	2.55 in
Weight	0.4 lb
Width	1.69 in

### Electrical Ratings

Amperage Rating	15 A
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 V
Voltage Rating Description	125 V
Wattage	1875 W

### Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

### Certifications And Compliance

Industry Standard(s)	Listed to UL Standard 498
Nema Rating	5-15P

### Logistics

Carton Quantity	10
Pallet Quantity	2560

### Product Assets

[Catalogs - WDK Catalog Full 2024](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK\_MX-UGP15231-SPEC-EN | REV 6/2024