



LazrSPEED®, OptiSPEED® Behind The Wall Pre-Radiused LC Connector for 0.9 mm Fiber, multimode

Product Classification

Portfolio	CommScope®
Brand	LazrSPEED® OptiSPEED®
Product Type	Fiber connector
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Construction Materials

Ferrule Geometry	Pre-radiused
Ferrule Material	Zirconia
Fiber Mode	Multimode

Dimensions

Compatible Cable Diameter	0.9 mm 0.0 in
Length	32.00 mm 1.26 in

General Specifications

Interface	LC
Body Style	BTW
Interface Feature	Standard
Color	Beige
Package Quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	0.45 kg @ 0 ° 1.00 lb @ 0 °
--	--------------------------------

Optical Performance

Insertion Loss, typical	0.17 dB
Return Loss, minimum	20.0 dB

Optical Specifications

Optical Components Standard	ANSI/TIA-568-C.3
------------------------------------	------------------

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

ISO 9001:2015

Classification

Compliant

Designed, manufactured and/or distributed under this quality management system

