



S29934

12T8/LED/48-830/DR
12 watt T8 LED; Medium bi-pin base; 3000K; 50000 Average
rated hours; 1700 lumens



Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube

S29934

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29934	045923299346	12	25W-32W	T8	Medium Bi-Pin	G13	12T8/LED/48-830/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	Gloss White	48"	1.00"	1700	50000	3000	Warm White
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed
82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	PL6UOQKEXHCD DLC Search	Yes	Yes
UL Classification						Warranty	