


Ground Clamps for Rigid Conduit With Conduit Hubs



Features

- Assembled with threaded hub for use on Rigid conduit pipe
- Corrosion resistant bronze construction

Applications


- Use to ground copper or aluminum wires to water pipes, ground rods, rebar or other structural members, ensuring a positive grounding connection to earth

Standard Material

- Bronze
- Screws - Zinc plated

Catalog Number	UPC	Size	Wire Range	Conduit Size	Hardware	Unit Carton	Ship Case	Weight/Case	A
621	16120	1/2" - 1"	#8 - #4	1/2"	Zinc plated	10	100	26	2.25
622	16130	1-1/4" - 2"	#8 - #4	1/2"	Zinc plated	5	50	35	3.60
623	16140	2-1/2" - 4"	#8 - #4	1/2"	Zinc plated	---	10	15	6.34
624	16150	5" - 6"	#8 - #4	1/2"	Zinc plated	---	10	20	8.50
621A	16160	1/2" - 1"	#8 - #4	3/4"	Zinc plated	5	50	20	2.25
622A	16170	1-1/4" - 2"	#8 - #4	3/4"	Zinc plated	5	50	37	3.60
623A	16180	2-1/2" - 4"	#8 - #4	3/4"	Zinc plated	---	10	12	6.34
624A	16190	5" - 6"	#8 - #4	3/4"	Zinc plated	---	10	21	8.50
621B	16200	1/2" - 1"	#8 - #4	1"	Zinc plated	---	10	9	2.25
622B	16210	1-1/4" - 2"	#8 - #4	1"	Zinc plated	---	10	10	3.60
623B	16220	2-1/2" - 4"	#8 - #4	1"	Zinc plated	---	10	21	6.34
624B	16230	5" - 6"	#8 - #4	1"	Zinc plated	---	10	28	8.50

Ground Rod Clamps For Direct Burial - Bronze



Features

- Approved for direct burial in ground and concrete
- Corrosion resistant bronze construction

Applications

- Securely connects a grounding conductor to a drive

Standard Material

- Bronze with stainless steel screw

Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B	Wire Size Min. Max.
411	13820	1/2"	100	500	9	1.22	.75	10 SOL 2 STR
412	13830	5/8"	100	500	18	1.41	.90	10 SOL 2 STR
413	13840	3/4"	---	50	12	1.47	1	10 SOL 2 STR