



Uniprise SLX Series Modular Jack, category 6, shielded , 4 Pair, without dust cover, gray

- Fits all existing SL panels and faceplates
- Universal latch for SL series
- 9 Different color options – Replaceable color caps
- Terminated with SL Series termination tool
- Wire holder cut off during termination
- Universal wiring label
- Easy re-termination

## Product Classification

<b>Portfolio</b>	Uniprise®
<b>Product Series</b>	SLX Series
<b>Product Type</b>	Modular jack
<b>Regional Availability</b>	North America

## Dimensions

<b>Compatible Cable Diameter, maximum</b>	8.50 mm   0.33 in
<b>Compatible Insulated Conductor Diameter, maximum</b>	1.600 mm   0.063 in
<b>Depth</b>	36.80 mm   1.45 in
<b>Height</b>	16.13 mm   0.64 in
<b>Width</b>	14.48 mm   0.57 in

## Electrical Specifications

<b>ANSI/TIA Category</b>	6
<b>Transmission Standard</b>	ANSI/TIA-568-C.2   ISO/IEC 11801 Class E

## Environmental Specifications

<b>Flammability Rating</b>	UL 94 V-0
<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)

## General Specifications

<b>Cable Type</b>	Shielded
<b>Color</b>	Gray
<b>Mount Type</b>	SL Series faceplates and panels
<b>Package Quantity</b>	24
<b>Packaging Type</b>	Bag   Box

Panel Cutout, recommended	14.78 x 20.07 mm (0.58 x 0.79 in)
Panel Thickness, recommended	1.60 mm

Mechanical Specifications

Conductor Gauge, solid	26–22 AWG
Conductor Gauge, stranded	26–24 AWG
Conductor Type	Solid   Stranded
Contact Base Material	Beryllium copper
Contact Plating Material	Gold
Contact Plating Thickness	1.27 µm
Material Type	Polycarbonate   ZMAC 5
Outlet Type	Standard
Termination Tool	SL Termination tool
Termination Type	IDC
Wiring	T568A   T568B

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant

