

# 3 Strand Twisted Yellow Polypropylene Rope

Premium grade U.V. stabilized polypropylene fiber

- Strong Lightweight Economical Rope
- Good Strength – Moderate Stretch
- Medium Laid – Balanced Construction
- Resistant to Rot, Mildew & Petroleum Products
- Stores Wet without Fiber Damage
- UV Stabilized Fiber
- Floats
- Continuous Length Long Length Reels Available
- Versatile



Part Number	Diameter in.	Length ft.	Minimum Break Strength lbs.	Approximate Density lbs./100 ft.	Approximate Package Weight lbs.
TWPY060600	3/16	600	720	0.7	4.2
TWPY061200	3/16	1,200	720	0.7	8.4
TWPY066000	3/16	6,000	720	0.7	42.0
TWPY080100	1/4	100	1,250	1.2	1.2
TWPY080300	1/4	300	1,250	1.2	3.6
TWPY080600	1/4	600	1,250	1.2	7.2
TWPY081200	1/4	1,200	1,250	1.2	14.4
TWPY082400	1/4	2,400	1,250	1.2	28.8
TWPY085000	1/4	5,000	1,250	1.2	60.0
TWPY100600	5/16	600	1,710	1.8	10.8
TWPY101200	5/16	1,200	1,710	1.8	21.6
TWPY120100	3/8	100	2,440	2.8	2.8
TWPY120300	3/8	300	2,440	2.8	8.4
TWPY120600	3/8	600	2,440	2.8	16.8
TWPY121200	3/8	1,200	2,440	2.8	33.6
TWPY122400	3/8	2,400	2,440	2.8	67.2
TWPY123600	3/8	3,600	2,440	2.8	100.8
TWPY160100	1/2	100	3,780	4.7	4.7
TWPY160300	1/2	300	3,780	4.7	14.1
TWPY160600	1/2	600	3,780	4.7	28.2
TWPY161200	1/2	1,200	3,780	4.7	56.4
TWPY162400	1/2	2,400	3,780	4.7	112.8
TWPY200100	5/8	100	5,600	7.5	7.5
TWPY200600	5/8	600	5,600	7.5	45.0
TWPY201200	5/8	1,200	5,600	7.5	90.0
TWPY202400	5/8	2,400	5,600	7.5	180.0
TWPY240100	3/4	100	7,650	10.7	10.7
TWPY240300	3/4	300	7,650	10.7	32.1

<b>Part Number</b>	<b>Diameter in.</b>	<b>Length ft.</b>	<b>Minimum Break Strength lbs.</b>	<b>Approximate Density lbs./100 ft.</b>	<b>Approximate Package Weight lbs.</b>
TWPY240600	3/4	600	7,650	10.7	64.2
TWPYTWPY241200	3/4	1,200	7,650	10.7	128.4
TWPY320100	1	100	12,600	18.0	18.0
TWPY320600	1	600	12,600	18.0	108.0
TWPY321200	1	1,200	12,600	18.0	216.0
TWPY340600	1-1/4	600	18,900	27.0	162.0
TWPY360600	1-1/2	600	26,800	38.0	230.0
TWPY400600	2	600	46,800	69.0	414.0