



(mast arm not included)

D-Series Size 1 Mast Arm Mount LED Area Luminaire



d"series

Specifications


EPA: 0.9 ft²
(0.08 m²)

Length: 27"
(68.6 cm)

Width: 13"
(33.0 cm)

Height: 5"
(12.7 cm)

Weight (max): 26 lbs
(11.8 kg)



A+ Capable options indicated by this color background.

Ordering Information

EXAMPLE: DSX1 LED 60C 1000 40K T3M MVOLT MA DDBXD

DSX1 LED								
Series	LEDs	Drive current	Color temperature	Distribution	Voltage	Mounting	Options	Finish (required)
DSX1 LED	Forward optics	530 530 mA	30K 3000 K (80 CRI min.)	T1S Type I short	MVOLT ¹	MA Mast arm ready	Shipped installed	DDBXD Dark bronze
	30C 30 LEDs (one engine)	700 700 mA	40K 4000 K (70 CRI min.)	T2S Type II short	120 ¹		(blank) No NEMA twist-lock receptacle (decorative cover), wildlife shield, trigger latch, and bridge fitter.	DBLXD Black
	40C 40 LEDs (two engines)	1000 1000 mA (1 A)	50K 5000 K (67 CRI)	T2M Type II medium	208 ¹		DMG 0-10V dimming extended out back of housing for external control (control ordered separate)	DNAXD Natural aluminum
	60C 60 LEDs (two engines)			T3S Type III short	240 ¹		PER NEMA twist-lock receptacle only (no controls) ³	DWHXD White
	Rotated optics			T3M Type III medium	277 ¹		DCR Dimmable and controllable via ROAM® (no controls) ⁴	DDBTXD Textured dark bronze
	60C 60 LEDs (two engines)			T4M Type IV medium	347 ²		HS House-side shield ⁵	DBLBXD Textured black
				TFTM Forward throw medium	480 ²		WTB Utility terminal block	DNATXD Textured natural aluminum
				T5VS Type V very short			DS Dual switching ^{6,7}	DWHGXD Textured white
				T5S Type V short			BUBLVL External bubble level	
				T5M Type V medium			L90 Left rotated optics ⁸	
				T5W Type V wide			R90 Right rotated optics ⁸	



Commercial Outdoor

One Lithonia Way • Conyers, Georgia 30012 • Phone: 1-800-705-7378 • www.lithonia.com
© 2012-2019 Acuity Brands Lighting, Inc. All rights reserved.

DSX1-MA-LED

Catalog
Number

Notes

Type

Hit the Tab key or mouse over the page to see all interactive elements.

A+ Capable Luminaire

This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and system-level interoperability.

- All configurations of this luminaire meet the Acuity Brands' specification for chromatic consistency
- This luminaire is A+ Certified when ordered with DTL® controls marked by a shaded background. DTL DLL equipped luminaires meet the A+ specification for luminaire to photocontrol interoperability¹
- This luminaire is part of an A+ Certified solution for ROAM®2 or XPoint™ Wireless control networks, providing out-of-the-box control compatibility with simple commissioning, when ordered with drivers and control options marked by a shaded background¹

To learn more about A+, visit www.acuitybrands.com/aplus.

1. See ordering tree for details.
2. A+ Certified Solutions for ROAM require the order of one ROAM node per luminaire. Sold Separately: [Link to Roam](#); [Link to DTL DLL](#)

Ordering Information

Accessories

Ordered and shipped separately.

SBOR 10 ODP BZ 3V	Pole-mounted motion/ambient sensor, 8-15' mounting height, MVOLT (specify finish)
SBOR 6 ODP BZ 3V	Pole-mounted motion/ambient sensor, 15-30' mounting height, MVOLT (specify finish)
DLL127F 1.5 JU	Photocell - SSL twist-lock, MVOLT ⁹
DLL347F 1.5 CUL JU	Photocell - SSL twist-lock (347V) ⁹
DLL480F 1.5 CUL JU	Photocell - SSL twist-lock (480V) ⁹
DSHORT SBK U	Shorting cap ⁹
DSX1HS 30C U	House-side shield for 30 LED unit
DSX1HS 40C U	House-side shield for 40 LED unit
DSX1HS 60C U	House-side shield for 60 LED unit

For more control options, visit [Sensor Switch](#), [DTL](#) and [ROAM](#) online.

Visit Lithonia Lighting's [POLES CENTRAL](#) to see our wide selection of poles, accessories and educational tools.

NOTES

- 1 MVOLT driver operates on any line voltage from 120-277V (50/60Hz).
- 2 Not available with single board, 530 mA product (30C 530 or 60C 530 DS). Not available with DCR.
- 3 That the PER option comes standard with a Shorting Cap.
- 4 Specifies a ROAM® enabled luminaire with 0-10V dimming capability; requires NEMA twist-lock receptacle. Not available with 347 or 480V. Additional hardware and services required for ROAM® deployment; must be purchased separately. Call 1-800-442-6745 or email: sales@roamservices.net.
- 5 Also available as a separate accessory; see Accessories information at left.
- 6 Requires two light engines. Provides 50% dimming capability via two independent drivers, each operating half the luminaire. N/A with PER, DCR, WTB or 530mA with 347v or 480v.
- 7 Requires an additional switched line.
- 8 Available with 60 LEDs (60C option) only.
- 9 Requires luminaire to be specified with PER option. Ordered and shipped as a separate line item.

