

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps
- Commercial Grade
- Large metal heatsink for optimal heat dissipation
- In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- Ideal for post top, bollards, and outdoor corridor lighting
- Environmentally friendly, no mercury used
- UL Listed, ENERGY STAR Compliant
- Non-Dimmable
- Universal Voltage 120 through 277V
- 50,000 hour Lifespan
- 5 Year No Compromise Warranty

Technical Specifications

<p>Performance</p> <p>Product Type: A-Line</p> <p>Input Wattage: 16.5W</p> <p>Lumens (Nominal): 2050lm</p> <p>Efficacy: 121 lm/W</p> <p>Color Accuracy (CRI): 80 CRI</p> <p>L70 Lifespan: 40,000 Hours</p>	<p>Dimmable: No</p> <p>Construction</p> <p>Bulb Shape: A21 E26</p> <p>Base Type: E26</p> <p>Beam Angle: 230°</p> <p>For Use Outdoors in Open Fixtures: No</p> <p>Other</p> <p>Equivalency: 125WW Incandescent</p>	<p>Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.</p> <p>LED Characteristics</p> <p>Color Temperature: 5000K Daylight</p> <p>Electrical</p> <p>Power Factor: >0.9</p> <p>Operating Temperature: -20°C - 45°C</p> <p>Input Voltage: 120-277V AC</p>
---	---	--

Technical Specifications (continued)

Electrical

Operating Frequency:

60 Hz

Electrical Characteristics

Input Current @ 120V:

178mA

Input Current @ 277V:

77mA

THD:

≤25%

Compliance

UL Listed:

Yes

UL Classified:

Yes

CEC Status:

Not lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	5.9	6.1	17.5
PALLET	1176	43.7	45.7	36.2

Dimension

