2.0 DESCRIPTION OF SYSTEM AND COMPONENTS


2.1 CORRUGATED STAINLESS STEEL TUBING

USE:

Corrugated Stainless Steel Tubing Conveys Gas

MATERIALS:

Tubing Stainless Steel Covering Polyethylene



SHAPE & DIMENSIONS

Custom Lengths Available Upon Request.

TUBING Size	10A 3/8″	15A 1/2″	20A 3/4″	25A 1″	32A 1-1/4″	38A 1-1/2″	50A 2″
EHD	15	19	25	30	37	48	62
Inner Dia. (D2) inches	.452	.591	.787	.984	1.26	1.59	2.12
Outside Dia. (D1) inches	.559	.724	.980	1.213	1.528	2.02	2.55
Tubing	REF	REF	REF	REF	REF	REF	REF
Thickness	.008	.008	.010	.010	.010	.012	.012
0.D. w/	REF	REF	REF	REF	REF	REF	REF
Covering (D0) inches	.606	.772	1.028	1.260	1.575	2.06	2.59
Length of	50,100	50,100	50,100	50,100	50,100	50,100	50,100
Tubing (Ft.)	250,500	250,500	180,250	180,250	250	150	150
	1,000	1,000	500	250			

2.1.1 MECHANICAL JOINTS

USE:


UPC

Mechanical Joint Fittings Connect the Corrugated Stainless Steel Tubing to a Manifold or Gas Outlet

MATERIALS:

Body: Brass
Nut: Brass
Retainer: Brass
Gasket: Composite Fiber





SHAPE & DIMENSIONS

FITTING	10M	15M	20M	25M	32M	38M	50M
Size	3/8″	1/2″	3/4″	1″	1-1/4″	1-1/2″	2″
TAPER THREAD (NPT)	1/2" or 3/8"	1/2" or 3/8"	1/2" 3/4" or 1"	3/4" or	1-1/4"	1-1/2"	2"

2.1.2 FEMALE MECHANICAL JOINTS


USE:

Female Mechanical Joint Join Corrugated Stainless Steel Tubing to Pipe Thread of the Same Size

MATERIALS:

Body: Brass Nut: Brass Retainer: Brass Gasket: Composite Fiber





SHAPE & DIMENSIONS

FITTING	10M	15M	20M	25M	
Size	3/8″	1/2″	3/4″	1″	
TAPER THREAD (NPT)	1/2"	1/2" or 3/8"	1/2" or 3/4"	3/4" or 1"	

2.1.3 COUPLINGS


USE:

Mechanical Couplings Join Two Corrugated Stainless Steel Tubings of the Same Size

MATERIALS:

Body: Brass Nut: Brass Retainer: Brass Gasket: Composite Fiber





SHAPE & DIMENSIONS

FITTING	10M	15M	20M	25M	32M	38M	50M
Size	3/8″	1/2″	3/4″	1″	1-1/4″	1-1/2″	2″
TAPER THREAD (NPT)	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"

