


# Straight blade power devices - 20, 30, 50 & 60A



Rating: Amps V/AC	Receptacle/ plug NEMA configuration	Flush receptacles	Wallplates	Surface receptacles	Panel mount receptacles	Plugs	Angle plugs
-------------------------	---	----------------------	------------	------------------------	-------------------------------	-------	-------------

## 3-pole, 4-wire grounding

20A 125/250V	 14-20R 14-20P	Industrial: <b>5759</b> (Black)					
30A 125/250V dryer	 14-30R 14-30P	Commercial: <b>1257</b> (Black)	Standard size: <b>39CH, 68, 2068, 2168, 93221, 93227</b>	Commercial: <b>1225</b> (Black)		Industrial: <b>5746N</b> (Gray)	Commercial: <b>S21</b> (Black)
		Industrial: <b>5744N</b> (Black)	Mid-size: <b>5068, PJ703, PJ724</b>				Industrial: <b>5732AN</b> (Gray)
30A 3Ø 250V	 15-30R 15-30P	Industrial: <b>8430N</b> (Black)	Standard size: <b>69, 5169, 93223</b>			Industrial: <b>8432N</b> (Gray)	Industrial: <b>8432AN</b> (Gray)
50A 125/250V range	 14-50R 14-50P	Commercial: <b>1258</b> (Black)	Standard size: <b>39CH, 68, 2068, 2168, 93221, 93227</b>	Commercial: <b>1212</b> (Black)	Commercial: <b>58</b> (Black)	Industrial: <b>5745N</b> (Gray)	Commercial: <b>S21</b> (Black)
		Industrial: <b>5754N</b> (Black)	Mid-size: <b>5068, PJ703, PJ724</b>				Industrial: <b>5752AN</b> (Gray)
50A 3Ø 250V	 15-50R 15-50P	Industrial: <b>8450N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Industrial: <b>8450P</b> (Black)	Industrial: <b>8452N</b> (Gray)	Industrial: <b>8452AN</b> (Gray)
60A 125/250V	 14-60R 14-60P	Industrial: <b>9460N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Commercial: <b>60</b> (Black)	Industrial: <b>9462N</b> (Gray)	Commercial: <b>S20</b> (Black)
							Industrial: <b>9462AN</b> (Gray)
60A 3Ø 250V	 15-60R 15-60P	Industrial: <b>8460N</b> (Black)	Standard size: <b>69, 5169, 93223</b>			Industrial: <b>AH8462N</b> (Gray)	Industrial: <b>AH8462AN</b> (Gray)

## 4-pole, 4-wire non-grounding

30A 3ØY 120/208V	 18-30R 18-30P					Industrial: <b>8332N</b> (Gray)	Industrial: <b>8332AN</b> (Gray)
50A 3ØY 120V/208V	 18-50R 18-50P					Industrial: <b>8352N</b> (Gray)	Industrial: <b>8352AN</b> (Gray)
60A 3ØY 120/208V	 18-60R 18-60P	Industrial: <b>5515N</b> (Black)	Standard size: <b>69, 5169, 93223</b>			Industrial: <b>5517N</b> (Gray)	Commercial: <b>S19</b> (Black)
							Industrial: <b>4516AN</b> (Gray)

Compliances, specifications and availability are subject to change without notice.

www.eaton.com  
www.eaton.com/arrowhart

All products on this page are RoHS compliant - Page Q-32

# Straight blade power devices 20, 30, 50 & 60A



Rating: Amps V/AC	Receptacle/ plug NEMA configuration	Flush receptacles	Wallplate	Surface receptacle	Panel mount receptacle	Plugs	Angle plugs
-------------------------	---	----------------------	-----------	-----------------------	---------------------------	-------	-------------

### 3-pole, 4-wire grounding

20A 125/250V	 14-20R	 14-20P	Industrial: <b>5759</b> (Black)				
30A 125/250V Dryer	 14-30R	 14-30P	Commercial: <b>1257</b> (Black)	Standard size: <b>39CH, 68, 2068, 2168, 93221, 93227</b>	Commercial: <b>1225</b> (Black)	Industrial: <b>5746N</b> (Gray)	Commercial: <b>S21</b> (Black)
			Industrial: <b>5744N</b> (Black)	Mid-size: <b>5068, PJ703, PJ724</b>			Standard size: <b>69, 5169, 93223</b>
30A 3Ø 250V	 15-30R	 15-30P	Industrial: <b>8430N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Industrial: <b>8432N</b> (Gray)	Industrial: <b>8432AN</b> (Gray)
50A 125/250V Range	 14-50R	 14-50P	Commercial: <b>1258</b> (Black)	Standard size: <b>39CH, 68, 2068, 2168, 93221, 93227</b>	Commercial: <b>1212</b> (Black)	Commercial: <b>58</b> (Black)	Commercial: <b>S21</b> (Black)
			Industrial: <b>5754N</b> (Black)	Mid-size: <b>5068, PJ703, PJ724</b>			Standard size: <b>69, 5169, 93223</b>
50A 3Ø 250V	 15-50R	 15-50P	Industrial: <b>8450N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Industrial: <b>8450P</b> (Black)	Industrial: <b>8452N</b> (Gray)
60A 125/250V	 14-60R	 14-60P	Industrial: <b>9460N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Commercial: <b>60</b> (Black)	Commercial: <b>S20</b> (Black)
						Industrial: <b>9462N</b> (Gray)	Industrial: <b>9462AN</b> (Gray)
60A 3Ø 250V	 15-60R	 15-60P	Industrial: <b>8460N</b> (Black)	Standard size: <b>69, 5169, 93223</b>		Industrial: <b>AH8462N</b> (Gray)	Industrial: <b>AH8462AN</b> (Gray)

### 4-pole, 4-wire, non-grounding

30A 3ØY 120/208V	 18-30R	 18-30P					Industrial: <b>8332N</b> (Gray)	Industrial: <b>8332AN</b> (Gray)
50A 3ØY 120/208V	 18-50R	 18-50P					Industrial: <b>8352N</b> (Gray)	Industrial: <b>8352AN</b> (Gray)
60A 3ØY 120/208V	 18-60R	 18-60P	Industrial: <b>5515N</b> (Black)	Standard size: <b>69, 5169, 93223</b>			Industrial: <b>5517N</b> (Gray)	Commercial: <b>S19</b> (Black)
							Industrial: <b>4516AN</b> (Gray)	

Power device dimensional information: B-22; Specification information: B-27-B-29  
Compliances, specifications and availability are subject to change without notice.

All products on this page are RoHS compliant - Page Q-32