ProLume® Plug-Ins

Halco LIGHTING TECHNOLOGIES

Halco's ProLume Plug-In CFLs are an energy efficient, long-life alternative to Incandescent lamps. They are available in Single and Double Tube 2-Pin; Single, Double, Triple and Spiral Tube 4-Pin; Flat Quad 4-Pin and High Lumen 4-Pin PLL. All Halco Plug-In CFLs use a tri-phosphor coating, which produces high CRI. These long life lamps are available in wattages from 5W to 57W with color temperatures ranging from 2700K to 5000K.

Specifications:

- Save up to 80% in energy costs compared to standard incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI
- Lead-free glass
- End-of-Life protection
- 2700, 3500, 4100 and 5000K
- 10,000 + Hours Average Rated Life
- Low maintenance
- TCLP compliant
- 1-Year Limited Warranty

» TCLP Compliant
» End-of-Life Protection
» 1-Year Limited Warranty

Markets:

- Residential
- Commercial

Applications:

- Wall sconces
- Down lighting
- Task lighting
- Security

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at halcolighting.com

Catalog Number: _____ Type: _____

Project: _____

Comments: _____ Date: _____

Prepared By: _____

Ordering Information

Watt	Base	Product #	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	MOL (inc)
Single Tube 2-Pin											
T4											
5 WATT	G23	109100	PL5S/27/ECO	Warm White	1/50	2700	82	250	210	12000	4.25"
5 WATT	G23	109102	PL5S/41/ECO	Cool White	1/50	4100	82	250	210	12000	4.25"
7 WATT	G23	109106	PL7S/27/ECO	Warm White	1/50	2700	82	400	335	12000	5.43"
7 WATT	G23	109107	PL7S/35/ECO	White	1/50	3500	82	400	335	12000	5.43"
7 WATT	G23	109108	PL7S/41/ECO	Cool White	1/50	4100	82	400	335	12000	5.43"
9 WATT	G23	109112	PL9S/27/ECO	Warm White	1/50	2700	82	600	505	12000	6.61"
9 WATT	G23	109144	PL9S/35/ECO	White	1/50	3500	82	600	505	12000	6.61"
9 WATT	G23	109116	PL9S/41/ECO	Cool White	1/50	4100	82	600	505	12000	6.61"
9 WATT	G23	109118	PL9S/50/ECO	Natural White	1/50	5000	82	600	505	12000	6.61"
13 WATT	GX23	109126	PL13S/27/ECO	Warm White	1/50	2700	82	825	695	12000	7.20"
13 WATT	GX23	109128	PL13S/35/ECO	White	1/50	3500	82	825	695	12000	7.20"
13 WATT	GX23	109130	PL13S/41/ECO	Cool White	1/50	4100	82	825	695	12000	7.20"
13 WATT	GX23	109132	PL13S/50/ECO	Natural White	1/50	5000	82	825	695	12000	7.20"
Single Tube 4-Pin Electronic											
T4											
13 WATT	2GX7	109134	PL13S/E/27/ECO	Warm White EOL	1/50	2700	82	825	695	12000	6.30"
13 WATT	2GX7	109136	PL13S/E/35/ECO	White EOL	1/50	3500	82	825	695	12000	6.30"
13 WATT	2GX7	109138	PL13S/E/41/ECO	Cool White EOL	1/50	4100	82	825	695	12000	6.30"
13 WATT	2GX7	109140	PL13S/E/50/ECO	Natural White EOL	1/50	5000	82	825	695	12000	6.30"
Double Tube 2-Pin											
T4											
9 WATT	G23-2	109110	PL9D/27/ECO	Warm White	1/50	2700	82	525	440	12000	4.25"
9 WATT	G23-2	109120	PL9D/41/ECO	Cool White	1/50	4100	82	525	440	12000	4.25"
13 WATT	GX23-2	109146	PL13D/27/ECO	Warm White	1/50	2700	82	900	755	12000	4.65"
13 WATT	GX23-2	109148	PL13D/35/ECO	White	1/50	3500	82	900	755	12000	4.65"
13 WATT	GX23-2	109150	PL13D/41/ECO	Cool White	1/50	4100	82	900	755	12000	4.65"
13 WATT	GX23-2	109149	PL13D/50/ECO	Natural White	1/50	5000	82	900	755	12000	4.65"
18 WATT	G24d-2	109152	PL18D/27/ECO	Warm White	1/50	2700	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109154	PL18D/35/ECO	White	1/50	3500	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109156	PL18D/41/ECO	Cool White	1/50	4100	82	1200	1010	12000	6.02"
18 WATT	G24d-2	109159	PL18D/50/ECO	Natural White	1/50	5000	82	1200	1010	12000	6.02"
T5											
22 WATT	GX32d-2	109862	PL22D/28	Warm White 15 mm Cluster	1/50	2800	82	1200	1010	10000	6.15"
22 WATT	GX32d-2	109864	PL22D/50	Natural White 15 mm Cluser	1/50	5000	82	1200	1010	10000	6.15"
T4											
26 WATT	G24d-3	109158	PL26D/27/ECO	Warm White	1/50	2700	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109160	PL26D/35/ECO	White	1/50	3500	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109162	PL26D/41/ECO	Cool White	1/50	4100	82	1800	1515	12000	6.77"
26 WATT	G24d-3	109163	PL26D/50/ECO	Natural White	1/50	5000	82	1800	1515	12000	6.77"
T5											
28 WATT	GX32d-3	109870	PL28D/28	Warm White 15 mm Cluster	1/50	2800	82	1800	1515	10000	6.60"
28 WATT	GX32d-3	109868	PL28D/50	Natural White 15 mm Cluster	1/50	5000	82	1800	1515	10000	6.60"
Double Tube 4-Pin Electronic											
T4											
13 WATT	G24q-1	109037	PL13D/E/27/ECO	Warm White EOL	1/50	2700	82	900	755	15000	5.16"
13 WATT	G24q-1	109035	PL13D/E/30/ECO	Soft White EOL	1/50	3000	82	900	755	15000	5.16"
13 WATT	G24q-1	109038	PL13D/E/35/ECO	White EOL	1/50	3500	82	900	755	15000	5.16"
13 WATT	G24q-1	109039	PL13D/E/41/ECO	Cool White EOL	1/50	4100	82	900	755	15000	5.16"
13 WATT	G24q-1	109122	PL13D/E/50/ECO	Natural White EOL	1/50	5000	82	900	755	15000	5.16"
18 WATT	G24q-2	109010	PL18D/E/27/ECO	Warm White EOL	1/50	2700	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109012	PL18D/E/35/ECO	White EOL	1/50	3500	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109013	PL18D/E/41/ECO	Cool White EOL	1/50	4100	82	1200	1010	15000	5.75"
18 WATT	G24q-2	109074	PL18D/E/50/ECO	Natural White EOL	1/50	5000	82	1200	1010	15000	5.75"
26 WATT	G24q-3	109090	PL26D/E/27/ECO	Warm White EOL	1/50	2700	82	1800	1515	15000	6.57"
26 WATT	G24q-3	109092	PL26D/E/35/ECO	White EOL	1/50	3500	82	1800	1515	15000	6.57"
26 WATT	G24q-3	109094	PL26D/E/41/ECO	Cool White EOL	1/50	4100	82	1800	1515	15000	6.57"
26 WATT	G24q-3	109096	PL26D/E/50/ECO	Natural White EOL	1/50	5000	82	1800	1515	15000	6.57"

Catalog Number: _____ Type: _____

Project: _____

Comments: _____ Date: _____

Prepared By: _____

Ordering Information

Watt	Base	Product #	Product Code	Description	Pkg. Qty.	Color Temp.	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	MOL (inc)
Triple Tube 4-Pin Electronic											
T4											
18 WATT	GX24q-2	44800	PL18T/E/27/ECO	Warm White EOL	1/50	2700	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44801	PL18T/E/35/ECO	White EOL	1/50	3500	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44803	PL18T/E/41/ECO	Cool White EOL	1/50	4100	82	1200	1010	15000	4.57"
18 WATT	GX24q-2	44804	PL18T/E/50/ECO	Natural White EOL	1/50	5000	82	1200	1010	15000	4.57"
26 WATT	GX24q-3	109020	PL26T/E/27/ECO	Warm White EOL	1/50	2700	82	1800	1515	15000	5.28"
26 WATT	GX24q-3	109022	PL26T/E/35/ECO	White EOL	1/50	3500	82	1800	1515	15000	5.28"
26 WATT	GX24q-3	109024	PL26T/E/41/ECO	Cool White EOL	1/50	4100	82	1800	1515	15000	5.28"
26 WATT	GX24q-3	109076	PL26T/E/50/ECO	Natural White EOL	1/50	5000	82	1800	1515	15000	5.28"
32 WATT	GX24q-3	109026	PL32T/E/27/ECO	Warm White EOL	1/50	2700	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109028	PL32T/E/35/ECO	White EOL	1/50	3500	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109030	PL32T/E/41/ECO	Cool White EOL	1/50	4100	82	2400	2015	15000	5.79"
32 WATT	GX24q-3	109070	PL32T/E/50/ECO	Natural White EOL	1/50	5000	82	2400	2015	15000	5.79"
42 WATT	GX24q-4	109032	PL42T/E/27/ECO	Warm White EOL	1/50	2700	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109034	PL42T/E/35/ECO	White EOL	1/50	3500	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109036	PL42T/E/41/ECO	Cool White EOL	1/50	4100	82	3200	2690	15000	6.61"
42 WATT	GX24q-4	109072	PL42T/E/50/ECO	Natural White EOL	1/50	5000	82	3200	2690	15000	6.61"
57 WATT	GX24q-5	44806	PL57T/E/27/ECO	Warm White EOL	1/50	2700	82	4200	3530	12000	7.57"
57 WATT	GX24q-5	44807	PL57T/E/41/ECO	Cool White EOL	1/50	4100	82	4200	3530	12000	7.57"
57 WATT	GX24q-5	44808	PL57T/E/50/ECO	Natural White EOL	1/50	5000	82	4200	3530	12000	7.57"
Spiral 4-Pin											
T3											
13 WATT	GX24q-1	109692	PL13SP/E/27	Warm White	1/50	2700	82	900	755	10000	3.74"
T3											
26 WATT	G24q-3	109696	PL26SP/E/27	Warm White	10/50	2700	82	1600	1345	10000	4.72"
26 WATT	G24q-3	109698	PL26SP/E/41	Cool White	10/50	4100	82	1600	1345	10000	4.72"
High Lumen Long 4-Pin											
T5											
18 WATT	2G11	109700	PLL18/835/ECO	White	10/40	3500	82	1250	1125	12000	8.94"
18 WATT	2G11	109702	PLL18/841/ECO	Cool White	10/40	4100	82	1250	1125	12000	8.94"
24 WATT	2G11	109704	PLL24/835/ECO	White	10/40	3500	82	1800	1620	12000	12.70"
24 WATT	2G11	109706	PLL24/841/ECO	Cool White	10/40	4100	82	1800	1620	12000	12.70"
36 WATT	2G11	109708	PLL36/835/ECO	White	10/40	3500	82	2800	2520	12000	16.45"
36 WATT	2G11	109710	PLL36/841/ECO	Cool White	10/40	4100	82	2800	2520	12000	16.45"
40 WATT	2G11	109712	PLL40/830/RS/ECO	Soft White	10/40	3000	82	3150	2835	20000	22.50"
40 WATT	2G11	109714	PLL40/835/RS/ECO	White	10/40	3500	82	3150	2835	20000	22.50"
40 WATT	2G11	109716	PLL40/841/RS/ECO	Cool White	10/40	4100	82	3150	2835	20000	22.50"
40 WATT	2G11	44900	PLL40/850/RS/ECO	Natural White	10/40	5000	82	3150	2835	20000	22.50"
55 WATT	2G11	109718	PLL55/835/ECO	White	10/40	3500	82	4700	4230	12000	21.20"
55 WATT	2G11	109720	PLL55/841/ECO	Cool White	10/40	4100	82	4700	4230	12000	21.20"
Flat Quad 4-Pin											
T5											
27 WATT	GX10q-4	109238	FML27/NDL	Natural White	1/50	5000	82	1700	1430	10000	5.90"

(Hg) Hg–LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Halco® LIGHTING TECHNOLOGIES

Atlanta | Carlstadt | Cleveland | Los Angeles | Houston | Phoenix

Halco Lighting Technologies | P.O. Box 2834 | Norcross, GA 30091-2834 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | halcolighting.com

© 2013 Halco Lighting Technologies, LLC. All rights reserved. 'where there's light, there's halco', Halco and ProLume are registered trademark of Halco Lighting Technologies.
All product names are trademarks or registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change.

Online Edition 10-14-13.