

SureCrimp® Aluminum Compression Lugs

Narrow Tang, 2 Hole, w/o Sight Hole

Conductor Range: 300kcmil - #4

RoHS
Compliant

UL
LISTED
453G

SA
LR-29601


A TYPE ALNN

Features

- Manufactured from high strength aluminum alloy
- Electro-Tin plated
- Chamfered entry
- Color coded end cap
- Ink marked
- Two bolt hole pattern
- Pre-filled with DE-OX® oxide inhibiting compound
- Range taking
- Narrow Tang
- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Dual rated AL9CU to 90° C

Benefits

- Offers maximum conductivity and excellent crimping characteristics
- Provides low contact resistance
- For easy conductor insertion
- Identifies the proper compression die
- For easy identification and proper location of crimps
- Provides maximum surface contact, secure attachment, and stabilization
- Prevents oxides from forming
- Permits inventories to be kept to a minimum
- Side by side mounting
- Application versatility
- For use with copper or aluminum conductor



Catalog Number	Wire Size	Expanded Wire Size*	Bolt Size	Stud Hole Dia.	Stud Hole Spacing	Dimensions							Die Color Code	Die Index
						A	B	C	D	G	O.D.	I.D.		
ALNN-4-14-1	#4 AWG	4-6 AWG	1/4	0.281 (7.1)	1.000 (25.4)	1.687 (42.8)	0.920 (23.4)	2.841 (72.2)	0.412 (10.5)	0.321 (8.2)	0.427 (10.8)	0.247 (6.3)	Green	375
ALNN-2-14-1	#2 AWG	2-6 AWG	1/4	0.281 (7.1)	1.000 (25.4)	1.687 (42.8)	0.970 (24.6)	2.943 (74.8)	0.495 (12.6)	0.321 (8.2)	0.525 (13.3)	0.307 (7.8)	Pink	348
ALNN-1-14-1	#1 AWG	1-2 AWG	1/4	0.281 (7.1)	1.000 (25.4)	1.687 (42.8)	0.970 (24.6)	2.987 (75.9)	0.514 (13.1)	0.321 (8.2)	0.544 (13.8)	0.358 (9.1)	Gold	471
ALNN-1/0-14-1	1/0 AWG	1/0-1 AWG	1/4	0.281 (7.1)	1.000 (25.4)	1.687 (42.8)	1.070 (27.2)	2.987 (75.9)	0.569 (14.5)	0.321 (8.2)	0.599 (15.2)	0.385 (9.8)	Tan	296
ALNN-2/0-38-1	2/0 AWG	2/0-1 AWG	3/8	0.406 (10.3)	1.000 (25.4)	1.937 (49.2)	1.355 (34.4)	3.688 (93.7)	0.644 (16.4)	0.414 (10.5)	0.674 (17.1)	0.432 (11.0)	Olive	297
ALNN-2/0-38-134	2/0 AWG	2/0-1 AWG	3/8	0.406 (10.3)	1.750 (44.5)	2.625 (66.7)	1.355 (34.4)	4.376 (111.2)	0.644 (16.4)	0.414 (10.5)	0.674 (17.1)	0.432 (11.0)	Olive	297
ALNN-3/0-38-1	3/0 AWG	3/0-1 AWG	3/8	0.406 (10.3)	1.000 (25.4)	1.937 (49.2)	1.355 (34.4)	3.731 (94.8)	0.731 (18.6)	0.414 (10.5)	0.761 (19.3)	0.495 (12.6)	Ruby	467
ALNN-3/0-38-134	3/0 AWG	3/0-1 AWG	3/8	0.406 (10.3)	1.750 (44.5)	2.625 (66.7)	1.355 (34.4)	4.419 (112.2)	0.731 (18.6)	0.414 (10.5)	0.761 (19.3)	0.495 (12.6)	Ruby	467
ALNN-3/0-12-134	3/0 AWG	3/0-1 AWG	1/2	0.562 (14.3)	1.750 (44.5)	3.000 (76.2)	1.355 (34.4)	4.794 (121.8)	0.731 (18.6)	0.546 (13.9)	0.761 (19.3)	0.495 (12.6)	Ruby	467
ALNN-4/0-38-1	4/0 AWG	4/0-1 AWG	3/8	0.406 (10.3)	1.000 (25.4)	1.937 (49.2)	1.535 (39.0)	3.963 (100.7)	0.824 (20.9)	0.414 (10.5)	0.854 (21.7)	0.553 (14.0)	White	298
ALNN-4/0-38-134	4/0 AWG	4/0-1 AWG	3/8	0.406 (10.3)	1.750 (44.5)	2.625 (66.7)	1.535 (39.0)	4.651 (118.1)	0.824 (20.9)	0.414 (10.5)	0.854 (21.7)	0.553 (14.0)	White	298
ALNN-4/0-12-1	4/0 AWG	4/0-1 AWG	1/2	0.562 (14.3)	1.000 (25.4)	2.125 (54.0)	1.535 (39.0)	4.151 (105.4)	0.824 (20.9)	0.546 (13.9)	0.854 (21.7)	0.553 (14.0)	White	298
ALNN-4/0-12-134	4/0 AWG	4/0-1 AWG	1/2	0.562 (14.3)	1.750 (44.5)	3.000 (76.2)	1.535 (39.0)	5.026 (127.7)	0.824 (20.9)	0.546 (13.9)	0.854 (21.7)	0.553 (14.0)	White	298
ALNN-250-38-1	250kcmil	250kcmil-1/0 AWG	3/8	0.406 (10.3)	1.000 (25.4)	1.937 (49.2)	1.535 (39.0)	4.003 (101.7)	0.894 (22.7)	0.414 (10.5)	0.924 (23.5)	0.595 (15.1)	Red	324
ALNN-250-38-134	250kcmil	250kcmil-1/0 AWG	3/8	0.406 (10.3)	1.750 (44.5)	2.625 (66.7)	1.535 (39.0)	4.691 (119.2)	0.894 (22.7)	0.414 (10.5)	0.924 (23.5)	0.595 (15.1)	Red	324
ALNN-250-12-1	250kcmil	250kcmil-1/0 AWG	1/2	0.562 (14.3)	1.000 (25.4)	2.125 (54.0)	1.535 (39.0)	4.191 (106.5)	0.894 (22.7)	0.546 (13.9)	0.924 (23.5)	0.595 (15.1)	Red	324
ALNN-250-12-134	250kcmil	250kcmil-1/0 AWG	1/2	0.562 (14.3)	1.750 (44.5)	3.000 (76.2)	1.535 (39.0)	5.066 (128.7)	0.894 (22.7)	0.546 (13.9)	0.924 (23.5)	0.595 (15.1)	Red	324
ALNN-300-38-1	300kcmil	300kcmil-2/0 AWG	3/8	0.406 (10.3)	1.000 (25.4)	1.937 (49.2)	1.535 (39.0)	4.059 (103.1)	0.980 (24.9)	0.414 (10.5)	1.010 (25.7)	0.650 (16.5)	Blue	470
ALNN-300-38-134	300kcmil	300kcmil-2/0 AWG	3/8	0.406 (10.3)	1.750 (44.5)	2.625 (66.7)	1.535 (39.0)	4.747 (120.6)	0.980 (24.9)	0.414 (10.5)	1.010 (25.7)	0.650 (16.5)	Blue	470
ALNN-300-12-1	300kcmil	300kcmil-2/0 AWG	1/2	0.562 (14.3)	1.000 (25.4)	2.125 (54.0)	1.535 (39.0)	4.247 (107.9)	0.980 (24.9)	0.546 (13.9)	1.010 (25.7)	0.650 (16.5)	Blue	470
ALNN-300-12-134	300kcmil	300kcmil-2/0 AWG	1/2	0.562 (14.3)	1.750 (44.5)	3.000 (76.2)	1.535 (39.0)	5.122 (130.1)	0.980 (24.9)	0.546 (13.9)	1.010 (25.7)	0.650 (16.5)	Blue	470

For Tool and Die Information Refer to Tooling Information Page Series: ALNS, ALND, ALNN, ASN

* When installed with specified dieless tools

** UL Listed 900kcmil compact Al Tested to UL 486A/B, UL File E6207