

Forged Brass • Hose Bibb • Ball Valve Type



- Manufactured in an ISO 9002 facility
- Rated for 200 PSI WOG
- Quarter turn operation
- Chrome plated brass ball
- 3/4" hose thread outlet
- Large flow rate
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Available in Handy Carton (HC) bin box packaging

Part No.	Valve Size	Inner Pack	Master Pack	Shipping Weight
103-023*	1/2"	10	100	43
103-024	3/4"	10	100	56
103-023HC*	1/2"	20	N/A	8
103-024HC	3/4"	20	N/A	11

❖ 1/2" Male external threads and 1/2" internal solder connection

Celcon® • Hose Bibb



- Rated for 150 PSI at -20° to 180°F
- For use w/ hot or cold water
- Not for use with compressed air
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Available in Handy Carton (HC) bin box packaging

Part No.	Valve Size	Inner Pack	Master Pack	Shipping Weight
Standard				
103-203	1/2"	12	72	14
103-204	3/4"	12	72	14
103-203HC	1/2"	25	N/A	5
103-204HC	3/4"	25	N/A	5
No Kink				
103-303	1/2"	12	72	13
103-304	3/4"	12	72	13
103-303HC	1/2"	20	N/A	4
103-304HC	3/4"	24	N/A	4

Brass • Hose Bibb • No Kink



- For use with water or oil
- Neoprene seal washer
- 3/4" hose thread outlet
- Large flow
- Pipe threads comply with ANSI B1.20.1
- Hose threads comply with ANSI B1.20.7
- Solder ends comply with ANSI B16.18
- Available in Handy Carton (HC) bin box packaging

Part No.	Valve Size	Inner Pack	Master Pack	Shipping Weight
Male Threaded				
102-303*	1/2"	12	72	31
102-304	3/4"	12	72	35
102-303HC*	1/2"	35	N/A	15
102-304HC	3/4"	30	N/A	15
Female Threaded				
102-403	1/2"	12	72	27
102-404	3/4"	12	72	31
102-403HC	1/2"	35	N/A	13
102-404HC	3/4"	30	N/A	13
Solder				
102-534*	1/2" & 3/4"	12	72	35
102-534HC*	1/2" & 3/4"	40	N/A	18

❖ 1/2" Male external threads and 1/2" internal solder connection

* 3/4" c x c coupling required for connection to 3/4" solder connection

Hose Bibb Handle



- Fits most standard and no kink hose bibbs
- Handy Carton (HC) bin box packaging

Part No.	Valve Size	Inner Pack	Master Pack	Shipping Weight
Heavy Duty				
888-122		1	170	5
Standard				
888-120HC		75	N/A	3