

Part No.	Size	Configuration	Model No.	Cs/Ct
----------	------	---------------	-----------	-------

**T-6800NL**  
**Pressure Reducing Valve with Serviceable Strainer Screen and Brass Bonnet**

No lead brass  
 Third-party tested and certified;  
 NSF / ANSI 61  
 ASSE 1003  
 CSA B356  
 CWP 300 psi (max)



111-323NL	1/2"	Union x FNPT	T-6800NL	24/1
111-324NL	3/4"	Union x FNPT	T-6800NL	24/1
111-325NL	1"	Union x FNPT	T-6800NL	16/1

**T-6801NL**  
**No Lead Brass Compact PRV, Thermoplastic Bonnet**

No lead brass  
 Third-party tested and certified;  
 NSF / ANSI 61  
 ASSE 1003  
 CSA B356  
 CWP 300 psi (max)



111-333NL	1/2"	FNPT Union x FNPT	T-6801NL	24/1
111-334NL	3/4"	FNPT Union x FNPT	T-6801NL	24/1
111-335NL	1"	FNPT Union x FNPT	T-6801NL	16/1

**T-6803NL**  
**No Lead Brass Compact PRV, Thermoplastic Bonnet**

No lead brass  
 Third-party tested and certified;  
 NSF / ANSI 61  
 ASSE 1003  
 CSA B356  
 CWP 300 psi (max)



111-033NL	1/2"	FNPT x FNPT	T-6803NL	24/1
111-034NL	3/4"	FNPT x FNPT	T-6803NL	24/1
111-035NL	1"	FNPT x FNPT	T-6803NL	16/1

**T-6803NL**  
**No Lead Brass Compact PRV, Brass Bonnet**

No lead brass  
 Third-party tested and certified;  
 NSF / ANSI 61  
 ASSE 1003  
 CSA B356  
 CWP 300 psi (max)



112-033NL	1/2"	FNPT x FNPT	T-6803NL	24/1
112-034NL	3/4"	FNPT x FNPT	T-6803NL	24/1
112-035NL	1"	FNPT x FNPT	T-6803NL	16/1

- ☰
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- #