

ProPress

Viega ProPress has helped installers across the world reduce installation time, save money and increase reliability on the job site. Built to last, Viega fittings are heavier than Type K copper and are available in sizes ranging from ½" to 4" in both copper and Zero Lead bronze. Viega's patented Smart Connect feature identifies unpressed connections during pressure testing so that they are not missed. Only Viega offers the Smart Connect feature.

FEATURES AND BENEFITS

- Connections are made in four to seven seconds
- Ensures a consistent, strong, reliable, watertight seal
- 50-year written warranty for non industrial and non marine applications
- Allows installers to join wet connections, making it the fastest solution for maintenance and repair
- Adaptable for any commercial, industrial or residential applications, whether new or retrofit
- Eliminates need for tanks, hoses, threading equipment, solder and flux
- Helps keep installations on or ahead of schedule
- Meets or exceeds the most rigorous codes and standards in North America

CODES AND STANDARDS

- NSF/ANSI 61: Drinking Water System Components – Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet ≤0.25% average lead content
- UL: Underwriters Laboratories
- ABS: American Bureau of Shipping
- CSA International: Canadian Standards Association
- IPC: International Plumbing Code
- UPC: Uniform Plumbing Code
- PHCC: National Standard Plumbing Code
- NFPA 13, 13D and 13R: Fire Sprinkler Applications
- FM: FM Global

ZERO LEAD

References to Zero Lead throughout this publication means product meeting the requirements of NSF 61-G through testing under NSF/ ANSI Standard 372 (0.25% or less percent maximum weighted average lead content). A few states already require meeting those requirements for plumbing fittings used in cooking and drinking water systems and federal law taking effect January 1, 2014 will make the requirements applicable to all states.

NOTE

A Green Dot on a Viega ProPress fitting indicates an EPDM sealing element



Viega ProPress Union
Smart Connect feature, Zero Lead
 - Bronze
 - Press connection, female pipe thread
Components
 Di-electric EPDM flat gasket
Model 2967ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.815	1	79155	8
3/4	3/4	1.146	1	79160	8
1	1	1.052	1	79165	8
1 1/4	1 1/4	1.536	1	79170	8
1 1/2	1 1/2	1.821	1	79175	8
2	2	2.826	1	79180	8



Viega ProPress Tailpiece
Smart Connect feature, Zero Lead
 - Bronze
 - Press connection, female union BSP
Components
 EPDM sealing element
Model 2957ZL

P	F BSP	Wt [lb]	Quantity	Part No	DG
1/2	1	0.218	1	79800	8
3/4	1	0.230	1	79805	8
1	1	0.309	1	79810	8
1	1 1/4	0.379	1	79815	8

Couplings



Viega ProPress Coupling
Stop
Smart Connect feature, Zero Lead
 - Copper
 - Press connection
Components
 EPDM sealing elements
Model 2915

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.080	10	78047	8
3/4	3/4	0.131	10	78052	8
1	1	0.163	5	78057	8
1 1/4	1 1/4	0.234	1	78062	8
1 1/2	1 1/2	0.472	1	78067	8
2	2	0.603	1	78072	8



Viega ProPress Coupling
XL, stop
Smart Connect feature, Zero Lead
 - Copper
 - Press connection
Components
 EPDM sealing elements
Note
 Must be installed with Viega ProPress XL-C rings and V2 actuator.
Model 0915XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	1.210	1	20728	8
3	3	1.668	1	20733	8
4	4	2.885	1	20738	8



Viega ProPress Coupling
No stop
Smart Connect feature, Zero Lead
 - Copper
 - Press connection
Components
 EPDM sealing elements
Model 2915.3

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.080	10	78172	8
3/4	3/4	0.131	10	78177	8
1	1	0.163	5	78182	8
1 1/4	1 1/4	0.231	1	78187	8
1 1/2	1 1/2	0.472	1	78192	8
2	2	0.603	1	78197	8



Viega ProPress Coupling
Extended, no stop
Smart Connect feature, Zero Lead
 - Copper
 - Press connection
Components
 EPDM sealing elements
Model 2915.5

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.136	5	79005	8
3/4	3/4	0.211	5	79010	8
1	1	0.284	5	79015	8
1 1/4	1 1/4	0.394	1	79020	8
1 1/2	1 1/2	0.679	1	79025	8
2	2	0.900	1	79030	8