

# BOSHART INDUSTRIES


Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164

Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

## NO LEAD BRONZE PITLESS ADAPTERS


PART NO.	MAKE	SIZE	DROP PIPE SIZE	CASING SIZE	HOLE SAW SIZE	WORKING LOAD-lbs	SHIPPING WGT-lbs	QUANTITY CTN	CASE
P-100NL	SEALWELL	1"	1"	5" - 12"	1-3/4"	2000	3.25	1	18
PA-100NL *	BII	1"	1"	5" - 12"	1-3/4"	2000	2.95	1	16
PA-800NL	BII	1"	1"	5" - 12"	1-3/4"	900	2.91	1	16
PA-125NL *	BII	1-1/4"	1-1/4"	5" - 12"	2-1/8"	2000	4.90	1	10
PA-200NL *	BII	2"	2"	5-5/8" - 12"	3-1/8"	5000	14.25	1	4

Note: 1-1/2" Pitless Adapter available in stainless steel (P-150SS)



## PRESSURIZED PITLESS ADAPTERS

- For installations requiring a pressurized point of attachment. A small hole between the internal and external gaskets ensures positive pressure at the seal to the well casing. Pressurized pitless are stamped with a "P" on the top of the slide portion of the pitless for identification after installation
- Approved for use in the State of Illinois



PART NO.	SIZE	DROP PIPE CONNECTION	WELL CASING SIZE RANGE	HOLE SAW SIZE	WORKING LOAD-lbs	SHIPPING WGT-lbs	QUANTITY CTN	CASE
PA-100-PNL *	1"	1"	5" - 12"	1-3/4"	2000	2.95	1	16
PA-125-PNL *	1-1/4"	1-1/4"	5" - 12"	2-1/8"	2000	4.90	1	10

## STAINLESS STEEL PITLESS ADAPTERS

- #304 Stainless Steel
- Large gasket for more efficient sealing on casing
- Chamfered slide for easy installation



PART NO.	MAKE	SIZE	DROP PIPE SIZE	CASING SIZE	HOLE SAW SIZE	WORKING LOAD-lbs	SHIPPING WGT-lbs	QUANTITY CTN	CASE
P-100-SS *	BII	1"	1"	5" - 12"	1-3/4"	6000	3.25	1	18
P-125-SS *	BII	1-1/4"	1-1/4"	5" - 12"	2-1/8"	6000	4.90	1	8
P-150-SS *	BII	1-1/2"	1-1/2"	5" - 12"	2-1/2"	6000	9.42	1	4
P-200-SS *	BII	2"	2"	5" - 12"	3-1/8"	6000	13.30	1	4

## DOUBLE DROP PIPE PITLESS ADAPTER

PART NO.	MAKE	DROP PIPE SIZE	CASING SIZE	HOLE SAW SIZE	WORKING LOAD-lbs	SHIPPING WGT-lbs	QUANTITY CTN	CASE
PA-2XNL *	BII	1" & 1-1/4"	4 1/2" - 12"	1-3/4" & 2-1/8"	2000	8.60	1	6

\*



## TAPPED PITLESS ADAPTERS - FOR UNDERGROUND TANKS / DIRTY WATER

PART NO.	SIZE	TAPPING	QUANTITY CTN	CASE
----------	------	---------	--------------	------

- 1" Tapped Pitless are for underground water well tank installations. The 1/4" FPT tapping provides a means to connect poly tubing to the pressure switch which is located near the buried tank.

P-100-SS-T	1" Stainless Steel	1/4"	1	16
------------	--------------------	------	---	----

Also available:

- 1-1/4" and 2" Tapped Pitless are for dirty water applications. The 1/4" FPT tapping provides a means to connect a 1/4" pipe to the pitless to allow easy removal of the pitless unit and pump. The pipe is guided by a rail/guide system that aligns the pitless elbow with the pitless slide when reinstalling (railing or guide system not included).

1-1/4" units are used with grinder pumps

P-125-SS-T	1-1/4" Stainless Steel	1/4"	1	8
------------	------------------------	------	---	---

2" units are used with all other sewage pumps

P-200-SS-T	2" Stainless Steel	1/4"	1	4
------------	--------------------	------	---	---

