

BOILER GAUGES PRESSURE/TEMPERATURE

Specially constructed for use on hot water heater boilers, these combination gauges give accurate indication of temperature and pressure. Gauges are designed to withstand the conditions normally encountered on domestic heating systems.



Dual scale: 60° - 260° F 20° - 120° C 3-1/2" diameter 1/2" MPT brass connection Steel case Glass face

		5
PART NUMBER	PSI	CONNECTION AND ELEMENT LENGTH
1451	0-75 PSI	2-3/4" Bottom mount
1452	10-75 F31	2-3/4" Back mount



Dual scale: 60° - 320° F 20° - 160° C 2-3/4" diameter 1/4" MPT brass connection Center backmount Polycarbonate face

		Back mount ONLY
PART	DOI	CONNECTION AND
NUMBER	PSI	ELEMENT LENGTH
1435	0-75 PSI	2-1/2"
1437	0-75 F3I	3-1/2"

DIAL TYPE THERMOMETERS

Economical - Backmount



Dual Scale:
40°-250°F, 0,-120°C,
Accuracy to 1°
5°Increments
2-1/2" Face
Brass wells
Choice of adapters
Thermometer can be removed from adapter for easy installation



PART NUMBER	CONNECTION
1449	1/2" MPT
1449-C	Well ONLY

#1450 SOLDER CONNECTION

PART NUMBER	CONNECTION
1450	3/4" CWT Solder
1450-W	Well ONLY

Thermometers supplied complete with connection

DIAL TYPE THERMOMETERS

Superior quality

Back or bottom mount
Dual scale:
32°-250°F, 0°-120°C
3-1/2" diameter
1/2" MPT brass connection
2-1/2" brass element (beyond MPT)
Corrosion resistant steel case





PART NUMBER	CONNECTION
1455	1/2" MPT CBM
1457	1/2" MPT Bottom