



General Fittings

General Fittings




P1186 DF

Part Number	"A" in (mm)	"B" in (mm)
P1186 DF	45° (0.79)	31/8" (79.4)



P2265 DF


Part Number	"A" in (mm)	"B" in (mm)	
P2265 DF	45° (0.79)	311/16" (93.7)	



P1048 DF


Part Number	"A" in (mm)	"B" in (mm)	Wt/100 pcs lbs (kg)
P1048 DF	7¼ (184.2)	41/8" (104.8)	105 (47.6)

P1045 DF




Wt/100 pcs: 55 lbs (24.9 kg)


P1047 DF




Wt/100 pcs: 88 lbs (39.9 kg)

P2072A DF, P2072A SQ DF







Wt/100 pcs: 373 lbs (169.2 kg)

Standard Dimensions for 15/8" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)
Hole Diameter: 9/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 17/8" (47.6mm); Width: 15/8" (41.3mm); Thickness: 1/4" (6.4mm)





16100 South Lathrop Avenue

Harvey, IL 60426

Office: 708-339-7814

Phone: 800-882-5543

Web: atkore.com/unistrut

CERTIFICATE OF COMPLIANCE BUY AMERICA BUY AMERICAN

June 1, 2023

To Whom It May Concern:

This certifies that Unistrut® channel is manufactured in the United States from steel melted and manufactured in the United States. These products comply with the Buy America requirements of 49 U.S.C. 5323{j}(I) and the applicable regulations in 49 CFR part 635.10 and with the Buy American Act of 1933 (FAR 52.225, Sections 9-12). All Unistrut channel finishes are also included as follows:

Plain (PL)
Pregalvanized Zinc (PG)
Hot Dip Galvanized (HG)
Electrocoated Zinc (EG)

Perma-Gold (ZD)
Unistrut Defender (OF)
Copper Clad (CC)
Perma-Green (GR)

Unistrut channel is also available in stainless steel and aluminum and meet both the Buy America and Buy American Acts.

While most Unistrut fittings are also certified as compliant with domestic requirements, please contact Industry Affairs with a specific bill of materials to confirm. Certification letters are also available to include a specific customer or project name upon request.

This certification has been issued for only the products listed above for domestic compliance and is valid for 180 days from date of issue. Alterations to this document by any agency other than Atkore International voids the certification.

Please contact IndustryAffairs@atkore.com if you have any questions.

Atkore Industry Affairs Team

Direct 1.800.882.5543

Email Industryaffairs@atkore.com