



RESIDENTIAL RECEPTACLES


Dust & Moisture Resistant & Clock Hanger Receptacles 15 & 20A, 125V




6207
shown with neoprene
sealing mat



S3713I



S3713TRI



R885TRWCC6

Features – Dust & Moisture Resistant


- Duplex receptacle has face backed by neoprene gasket which is slit to provide wiping action on plug blades and to provide positive closure when not in use.
- Cellular neoprene sealing mat fits under wall plate.

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.			UL498	FSUL WC596	C22.2 No. 42
DUST & MOISTURE RESISTANT							
6207	15	125	Duplex, Dust and Moisture Resistant, Gray	5-15R	•	•	•
6307	20	125	Duplex, Dust and Moisture Resistant, Gray	5-20R	•	•	•
CR6307	20	125	Duplex, Corrosion, Dust and Moisture Resistant, Yellow	5-20R	•	•	•

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.			UL498	FSUL WC596	C22.2 No. 42
CLOCK HANGERS							
S3713I	15	125	Recessed Receptacle with Ivory Smooth Wall Plate	5-15R	•	•	•
S3713W	15	125	Recessed Receptacle with White Smooth Wall Plate	5-15R	•	•	•
S3713GRY	15	125	Recessed Receptacle with Gray Smooth Wall Plate	5-15R	•	•	•
S3713BK	15	125	Recessed Receptacle with Black Smooth Wall Plate	5-15R	•	•	•
S3713LA	15	125	Recessed Receptacle with Light Almond Smooth Wall Plate	5-15R	•	•	•
S3733SS	15	125	Recessed Receptacle with Stainless Steel Wall Plate	5-15R	•	•	•
S3733	15	125	Recessed Receptacle with Brass Wall Plate	5-15R	•	•	•
TAMPER-RESISTANT CLOCK HANGERS BACK & SIDE WIRE							
S3713TRI	15	125	Recessed Receptacle with Ivory Smooth Wall Plate	5-15R	•	•	•
S3713TRW	15	125	Recessed Receptacle with White Smooth Wall Plate	5-15R	•	•	•
S3713TRGRY	15	125	Recessed Receptacle with Gray Smooth Wall Plate	5-15R	•	•	•
S3713TRBK	15	125	Recessed Receptacle with Black Smooth Wall Plate	5-15R	•	•	•
S3713TRLA	15	125	Recessed Receptacle with Light Almond Smooth Wall Plate	5-15R	•	•	•

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE
	A.	V.			cULus
RECESSED DUPLEX TAMPER-RESISTANT RECEPTACLE					
R885TRWCC6	15	125	White	5-15R	•

2 Pole, 3 Wire



STRAIGHT BLADE RECEPTACLES

RESIDENTIAL RECEPTACLES

Power Outlet Receptacles & Plugs 20, 30, 50, & 60A

RATING		RECEPTACLE/PLUG CONFIGURATION & NEMA NO.							
A.	V.		FLUSH RECEPTACLE	WALL PLATE <small>*For 2 screw mounting **For 4 screw mounting</small>	SURFACE RECEPTACLE	PLUG	ANGLE PLUG	CONNECTOR	
			CATALOG NUMBERS						
2 POLE, 3 WIRE GROUNDING									
30	125	5-30			3802 § AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**		D0531 .57"-1.26"	D0533 .57"-1.26"
30	125	NEMA TT30			3830 AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**			
For recreational vehicles.									
30	250	6-30			3801 AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**		D0631 .57"-1.26"	3869 D0633 .57"-1.26"
50	125	5-50						D0551 .57"-1.26"	D0553 .57"-1.26"
50	250	6-50			3804 § AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**	3852 # AL/CU	D0651 .57"-1.26"	3869 D0653 .57"-1.26"
3 POLE, 3 WIRE NON-GROUNDING									
30	125/250 Dryer	10-30			3860 AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**	388 AL/CU	1031	3861
50	125/250 Range	10-50			3890 § AL/CU	1-Gang: TP724* 2-Gang: SS702* 2-Gang: TP703**	385 AL/CU	1051 .57"-1.26"	3861 1053 .32"-.91"
3 POLE, 4 WIRE GROUNDING									
20	125/250	14-20			3820	1-Gang: SS7*			
30	125/250 Dryer	14-30			3864 AL/CU 3864NA †	2-Gang: SS702* 2-Gang: TP703**	3884 #/388440‡ AL/CU	1431 .57"-1.26"	5746AN 3867
30	3ø, 250	15-30			5740 AL/CU	2-Gang: SS702* 2-Gang: TP703**			5741AN
50	125/250 Range	14-50			3894 § AL/CU 3894NA †	2-Gang: SS702* 2-Gang: TP703**	3854 #/385440‡ AL/CU	1451 .57"-1.26"	5745AN 3867
50	3ø, 250	15-50			5750 AL/CU	2-Gang: SS702* 2-Gang: TP703**			5751AN
60	3ø, 250	15-60			5760 AL/CU	2-Gang: SS702* 2-Gang: TP703**		8462N	5761AN
4 POLE, 4 WIRE NON-GROUNDING									
20	3øY, 120/208	18-20			3822	1-Gang: SS7*		7251DF .35"-1.05"	
60	3øY, 120/208	18-60			3870 § AL/CU	2-Gang: SS701**		D1861 .57"-1.26"	8302AN

‡ In bulk pack of 40 with plastic snap-in wire clamp.

§ Up to #3 AWG aluminum conductors.

Up to #4 AWG aluminum conductors.


For further information consult Wall Plate Section I (for Stainless Steel versions of TP724 and TP703, refer to Pages I-10 and I-11).

† NAFTA-Compliant Receptacles are ideal for use on projects subject to the provisions of the Buy American Act.


All devices listed on this page conform to NEMA WD-1 and WD-6.

RESIDENTIAL RECEPTACLES

Power Outlet Receptacles & Plugs 20, 30, 50, & 60A




3822




3820




385 3854
388 3884
3852




3870




3801 3802
3804 3864
3894 5740
5750 5760




3830
3860
3890




3861




3867



3869



5741AN 5751AN
5745AN 5761AN
5746AN 8302AN



7251DF

STRAIGHT BLADE RECEPTACLES