

L1420R -- Locking Receptacle



Hubbell-Pro locking devices provide a safe disconnect solution between an equipment load and a power source. These devices incorporate a locking interface that is engaged and disengaged simply by rotating the device assuring a safe and reliable electrical connection.

Product Specifications

SELECTSPEC Product Type	Locking Devices
Locking Device Product	Receptacle
Locking Device Rating	20A, 125/250V
Locking Device Wiring Scheme	3 Pole, 4 Wire Grounding
Locking Device NEMA Configuration	L14-20R
Locking Device Color	Black
Locking Device Listings and Approvals	UL Listed, CSA Certified
Features	Nylon Construction, Visible NEMA Ratings, Nickel Plated Receptacle Strap
Face	High Impact-Resistant Chemical-Resistant Nylon
Base	Reinforced Thermoplastic Polyester
Contacts/Blade Material	Rivetless Copper Alloy
Mounting Yoke	Nickel Plated Steel
Dielectric Voltage	Withstands 3,000V per UL498
Max Working Voltage	600V AC, 250V DC
Current Interrupting	Capable of withstanding a fault level of 1000A circuit, per UL 498.
Temperature Rise	Maximum 30 deg C. temperature rise at full rated current after 50 cycles overload at 150% rated current for either AC or DC applications per UL 498
Overload	Minimum 4.8 times rated current for 100 cycles.
Terminal Identification	Terminals identified in accordance with UL 498 (Brass, White, Green).
Terminal Accommodation	#14 to #8 AWG Solid or Stranded Copper Wire.
Product Identification	Ratings and NEMA identification are permanently marked on device.
Flammability	UL 94 V2 Minimum
Operating Temperatures	Continuous use without impact -40 deg C to 85 deg C
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

