



# COMMERCIAL GRADE RECEPTACLES


## Hard Use Specification Grade Receptacles 15A & 20A, 125 & 125/250V



5262I



5362GN



PT5362LA



### PlugTail® Features Only


- .036 inch thick, brass, triple-wipe power contacts for lasting retention.
- Plated steel wrap-around strap design for maximum durability and corrosion resistance.  
No exposed terminals create a finger safe application before, during, and after installation.
- Built-in connector features large brass terminal blades to ensure consistent, reliable electrical connections.
- Crimped and welded contacts.
- Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing.
- Large brass contacts snugly terminate on device blade terminals.
- Pre-stripped connector leads fasten to conductors, easier than standard pigtailed.
- Auto-ground clip assures positive ground.
- **PlugTail devices** install up to 5 times faster than traditional.

### Features

- Corrosion-resistant, plated and tabbed steel strap is locked in to face and back body to resist pulling away from face/body assembly.
- .032 inch thick, brass, triple-wipe power contacts for lasting retention.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- Impact-resistant nylon face.
- 8 hole internal screw-pressure-plate back wire terminals accept #10 – 14 AWG solid or stranded copper or copper-clad conductors.
- Terminal compartments isolated from each other for positive conductor containment.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.


CATALOG NUMBER	PLUGTAIL CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
		A.	V.			UL498	FSUL WC596	C22.2 No. 42
<b>DUPLEX RECEPTACLES</b>								
5262I	PT5262I	15	125	Ivory	5-15R	•	•	•
5262W	PT5262W	15	125	White	5-15R	•	•	•
5262	PT5262	15	125	Brown	5-15R	•	•	•
5262GRY	PT5262GRY	15	125	Gray	5-15R	•	•	•
5262BK	PT5262BK	15	125	Black	5-15R	•	•	•
5262RED	PT5262RED	15	125	Red	5-15R	•	•	•
5262BL	PT5262BL	15	125	Blue	5-15R	•	•	•
5262LA	PT5262LA	15	125	Light Almond	5-15R	•	•	•
5362I	PT5362I	20	125	Ivory	5-20R	•	•	•
5362W	PT5362W	20	125	White	5-20R	•	•	•
5362	PT5362	20	125	Brown	5-20R	•	•	•
5362GRY	PT5362GRY	20	125	Gray	5-20R	•	•	•
5362BK	PT5362BK	20	125	Black	5-20R	•	•	•
5362RED	PT5362RED	20	125	Red	5-20R	•	•	•
5362LA	PT5362LA	20	125	Light Almond	5-20R	•	•	•
5362BL	PT5362BL	20	125	Blue	5-20R	•	•	•
5362GN		20	125	Green	5-20R	•	•	•
5362YLW		20	125	Yellow	5-20R	•	•	•
5362OR		20	125	Orange	5-20R	•	•	•
<b>COMBINATION DUPLEX RECEPTACLES SIDE WIRE</b>								
5290I		15	125/250	Ivory	5/6-15R	•	•	•
5290		15	125/250	Brown	5/6-15R	•	•	•
5890I		20	125/250	Ivory	5/6-20R	•	•	•
5890W		20	125/250	White	5/6-20R	•	•	•
5890		20	125/250	Brown	5/6-20R	•	•	•

### 2 Pole, 3 Wire



NEMA 5-15R

NEMA 5-20R



NEMA 6-15R

NEMA 6-20R

For PlugTail Connectors, see Page B-21.

For Bulk Packaging Solutions consult factory.

All devices listed on this page conform to NEMA WD-1 and WD-6.