


Universal Strut Clamps

EMT, IMC and Rigid - One Piece Design



Catalog Number	UPC	Size	Ship Case	Weight/ Case	A	B
2101CS	87280	1/2"	100	10	1.24	2.23
2102CS	87281	3/4"	100	12	1.24	2.42
2103CS	87282	1"	100	13	1.24	2.77
2104CS	87283	1-1/4"	100	15	1.24	3.09
2105CS	87284	1-1/2"	50	9	1.24	3.38
2106CS	87285	2"	50	10	1.24	3.77
2107CS	87286	2-1/2"	50	14	1.24	4.47
2108CS	87287	3"	25	16	1.24	5.08
2109CS	87288	3-1/2"	25	18	1.24	5.74
2110CS	87289	4"	25	19	1.24	6.30

Features

- Strengthening ribs for heavier loads
- For use with EMT/Rigid and IMC conduit
- One piece clean design for easier handling
- Plastic retainer attached for avoiding accidental loss of high strength bolt during installation
- Integral threads on clamp without nut to save installation time

Applications

- Use to secure EMT, IMC, and Rigid conduits


Standard Material

- Steel

Standard Finish

- Zinc plated

EMT and Rigid



Catalog Number	UPC	Size	Screw Size	Ship Case	Weight/ Case	A	B
2101	41031	1/2"	1/4-20 x 1-1/4"	100	10	1.24	2.30
2102	41032	3/4"	1/4-20 x 1-1/4"	100	11	1.24	2.46
2103	41033	1"	1/4-20 x 1-1/4"	100	13	1.24	2.68
2104	41034	1-1/4"	1/4-20 x 1-1/4"	100	16	1.24	3.21
2105	41035	1-1/2"	5/16-18 x 1-1/2"	50	9	1.24	3.42
2106	41036	2"	5/16-18 x 1-1/2"	50	11	1.24	4
2107	41037	2-1/2"	5/16-18 x 1-3/4"	50	17	1.24	5
2108	41038	3"	5/16-18 x 1-3/4"	25	21	1.24	5.55
2109	41039	3-1/2"	5/16-18 x 1-3/4"	25	13	1.24	6
2110	41040	4"	5/16-18 x 1-3/4"	25	15	1.24	6.50

Features

- For use with EMT/Rigid and IMC conduit
- All screws - 5/16" x 1-1/4" slotted hex head

Applications

- Use to support stationary pipe and tubing lines from strut channel

Standard Material

- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014