

Rigid Locknuts

Zinc Die Cast

Features


- Tightens without deformation
- Serrated teeth prevent loosening from vibrations

Applications

- Affixes Rigid conduit to an electrical box or other metal enclosure
- To connect externally threaded conduit connector to a threadless opening in a box or enclosure

Standard Material

- Zinc die cast



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/ Case	Inches		
							A	B	Thread Pitch Diameter
241	12040	1/2"	14	200	2,000	20	1.12	.15	.787 - .797
242	12050	3/4"	14	100	1,000	20	1.33	.15	.999 - 1.009
243	12060	1"	11-1/2	100	1,000	20	1.68	.19	1.25 - 1.26
244	12070	1-1/4"	11-1/2	50	500	20	2.15	.19	1.595 - 1.605
245	12080	1-1/2"	11-1/2	50	500	20	2.35	.19	1.837 - 1.847
246	12090	2"	11-1/2	50	200	12	2.89	.19	2.307 - 2.317
247	12100	2-1/2"	8	25	100	13	3.43	.25	2.777 - 2.788
248	12110	3"	8	25	100	18	4.12	.25	3.403 - 3.414
249	12120	3-1/2"	8	10	40	13	4.67	.27	3.892 - 3.904
250	12130	4"	8	10	40	15	5.25	.27	4.399 - 4.411