


Straight Liquidtight Connectors With Insulated Throat - Malleable Iron



Features

- Liquidtight, raintight, oiltight
- Tapered threaded male hub NPT
- Insulated throat protects conductors from abrasion damage
- Compact slim diameter with small turning radius
- Zinc electro plated for excellent durability

Applications

- To secure, ground and seal liquidtight conduit to a box or enclosure
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class I Div.2, Class II Div.1 and 2, Class III Div.1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1

Standard Material

- Malleable iron
- Steel locknut

Standard Finish

- Zinc plated


Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014

Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
470S	14430	3/8" 1/2" KO	20	200	31	1.18	1.72
471S	14440	1/2"	20	200	33	1.36	1.73
472S	14450	3/4"	10	100	25	1.61	1.81
473S	14460	1"	5	50	18	1.89	1.85
474S	33620	1-1/4"	5	50	28	2.39	2.05
475S	33630	1-1/2"	2	20	15	2.62	2.38
476S	33640	2"	2	20	22	3.24	2.49
477S	33650	2-1/2"	---	1	2	3.89	3.21
478S	33660	3"	---	1	3	4.74	3.37
479S	33670	3-1/2"	---	1	4	5.31	3.40
480S	33680	4"	---	1	5	5.82	3.66
480SA*	85294	5"	---	1	10	6.06	4.63
480SB*	85324	6"	---	1	13	7.75	4.94

*480SA and 480SB not UL listed

With Insulated Throat - Steel



Features

- Liquidtight, raintight, oiltight
- Industrial specification grade, screw machined steel
- Corrosion resistant protection from moisture & oils

Applications

- Bonds liquidtight conduit to box or enclosure
- Straight type

Standard Material

- Steel

Standard Material

- Zinc plated

UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class I Div. 2, Class II Div. 1 and 2, Class III Div. 1 and 2 are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1

Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight Case	A	B	C
470ST	14439	3/8" 1/2" KO	20	200	25	1.09	1.19	.63
471ST	14441	1/2"	20	200	31	1.19	1.34	.63
472ST	14451	3/4"	10	100	23	1.43	1.43	.63
473ST	14461	1"	5	50	18	1.75	1.63	.66
474ST	14471	1-1/4"	5	50	23	2.16	1.84	.67
475ST	14481	1-1/2"	2	20	12	2.38	2	.72
476ST	14491	2"	2	20	15	2.88	2.13	.72