



CAT#	A	B	C
470S	1.38	.56	1.69
471S	1.38	.59	1.69
472S	1.64	.63	1.81
473S	1.91	.75	2.13
474S	2.44	.78	2.19
475S	2.72	.91	2.44
476S	3.25	1.00	2.88
477S	4.00	1.50	3.25
478S	4.63	1.50	3.88
479S	5.50	1.50	4.00
480S	5.82	1.63	4.00



CAT#	A	B	C
490S	1.31	1.81	.50
491S	1.41	1.88	.50
492S	1.63	2.06	.53
493S	2.06	2.25	.69
494S	2.13	2.75	.72
495S	2.69	3.13	.84
496S	2.94	3.88	.94
497S	6.00	6.50	1.50
498S	6.50	7.00	1.50
500S	9.00	9.50	1.50



CAT#	A	B	C	D
230S	.50	1.38	1.38	1.00
231S	.50	1.38	1.38	1.06
232S	.53	1.64	1.50	1.19
233S	.69	1.91	1.69	1.38
234S	.72	2.44	1.94	1.63
235S	.84	2.72	2.25	1.81
236S	.94	3.25	2.75	1.94
237S	1.50	4.00	4.00	3.50
238S	1.50	4.63	4.50	4.00
239S	1.63	5.81	5.00	4.50
240S	1.63	5.81	5.00	4.50

LIQUID TIGHT CONNECTORS

INSULATED THROAT-COMPONENT TYPE

MALLEABLE IRON

TOPAZ CAT #	UPC#	CONDUIT SIZE	UNIT CTN	SHIP CASE	WT/ CASE
STRAIGHT					
470S	14430	3/8" 1/2" KO	25	250	25
471S	14440	1/2"	20	200	26
472S	14450	3/4"	10	100	18
473S	14460	1"	5	50	16
474S	33620	1 1/4"	5	50	37
475S	33630	1 1/2"	2	20	21
476S	33640	2"	2	20	33
477S	33650	2 1/2"	—	1	3
478S	33660	3"	—	1	4
479S	33670	3 1/2"	—	1	4
480S	33680	4"	—	1	5

DOWNLOAD SPEC SHEET



90° ANGLE

490S	14790	3/8" 1/2" KO	10	100	26
491S	14800	1/2"	10	100	26
492S	14810	3/4"	10	100	24
493S	14820	1"	5	50	34
494S	33690	1 1/4"	2	20	24
495S	33700	1 1/2"	2	20	40
496S	33710	2"	1	20	28
497S	33720	2 1/2"	—	1	7
498S	33730	3"	—	1	11
500S	33750	4"	—	1	10

DOWNLOAD SPEC SHEET



45° ANGLE

230S	11960	3/8" 1/2" KO	10	100	24
231S	11970	1/2"	10	100	28
232S	11980	3/4"	10	100	42
233S	11990	1"	5	50	32
234S	33550	1 1/4"	2	20	22
235S	33560	1 1/2"	2	20	32
236S	33570	2"	2	20	49
237S	33580	2 1/2"	—	1	5
238S	33590	3"	—	1	7
239S	33591	3 1/2"	—	1	10
240S	33610	4"	—	1	12

DOWNLOAD SPEC SHEET



UL rated suitable for hazardous locations.
Class I, Div. 2; Class II, Div. 1 and 2; Class III, Div. 1 and 2;
NEC 501-4(b), 502-4(a) (2), 503-3(a)

LIQUID TIGHT