


# Rigid Straps

## Snap-On Type - One Hole - Steel




| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | A     | B    |
|----------------|-------|---------------|-------------|-----------|-------------|-------|------|
| <b>531A**</b>  | 15041 | <b>1/4"</b>   | 100         | 1000      | 14          | 1.51  | .562 |
| <b>531B**</b>  | 15045 | <b>3/8"</b>   | 100         | 1000      | 12          | 1.81  | .562 |
| <b>531</b>     | 15050 | <b>1/2"</b>   | 50          | 500       | 17          | 1.91  | .625 |
| <b>532</b>     | 15060 | <b>3/4"</b>   | 50          | 500       | 25          | 2.21  | .75  |
| <b>533</b>     | 15070 | <b>1"</b>     | 25          | 250       | 18          | 2.57  | .875 |
| <b>534</b>     | 15080 | <b>1-1/4"</b> | 20          | 200       | 18          | 2.79  | .88  |
| <b>535</b>     | 15090 | <b>1-1/2"</b> | 20          | 200       | 31          | 3.69  | .899 |
| <b>536</b>     | 15100 | <b>2"</b>     | 10          | 100       | 24          | 4.17  | 1.14 |
| <b>517*</b>    | 15670 | <b>2-1/2"</b> | ---         | 50        | 21          | 5     | 1.28 |
| <b>518*</b>    | 15680 | <b>3"</b>     | ---         | 25        | 12          | 5.55  | 1.28 |
| <b>519*</b>    | 15690 | <b>3-1/2"</b> | ---         | 25        | 17          | 6.37  | 1.28 |
| <b>520*</b>    | 15700 | <b>4"</b>     | ---         | 25        | 17          | 6.87  | 1.28 |
| <b>520A**</b>  | 15702 | <b>5"</b>     | ---         | 10        | 17          | 9     | 1.50 |
| <b>520B**</b>  | 15704 | <b>6"</b>     | ---         | 10        | 20          | 10.35 | 1.50 |

\*EMT and Rigid

\*\*Not UL Listed

## Snap-On Type - Two Hole - Steel



| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | A     | B    |
|----------------|-------|---------------|-------------|-----------|-------------|-------|------|
| <b>541</b>     | 15150 | <b>1/2"</b>   | 50          | 500       | 9           | 2.43  | .625 |
| <b>542</b>     | 15160 | <b>3/4"</b>   | 50          | 500       | 12          | 2.81  | .685 |
| <b>543</b>     | 15170 | <b>1"</b>     | 25          | 250       | 9           | 3.28  | .75  |
| <b>544</b>     | 15180 | <b>1-1/4"</b> | 20          | 200       | 16          | 4.02  | .875 |
| <b>545</b>     | 15190 | <b>1-1/2"</b> | 10          | 100       | 14          | 4.58  | 1    |
| <b>546</b>     | 15200 | <b>2"</b>     | ---         | 50        | 5           | 5.22  | 1    |
| <b>527*</b>    | 15010 | <b>2-1/2"</b> | ---         | 25        | 4           | 5.87  | 1.43 |
| <b>528*</b>    | 15020 | <b>3"</b>     | ---         | 25        | 5           | 6.50  | 1.75 |
| <b>529*</b>    | 15030 | <b>3-1/2"</b> | ---         | 25        | 7           | 7.12  | 2    |
| <b>530*</b>    | 15040 | <b>4"</b>     | ---         | 25        | 7           | 7.75  | 2.25 |
| <b>530A</b>    | 15042 | <b>5"</b>     | ---         | 10        | 16          | 10.60 | 1.25 |
| <b>530B</b>    | 15044 | <b>6"</b>     | ---         | 10        | 7           | 11.85 | 1.25 |

\* EMT and Rigid

### Features

- Snap-on type Rigid strap with one hole
- Inverted rib for strength
- Easy to install

### Applications

- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

### Standard Material

- Steel

### Standard Finish

- Zinc plated

### Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014

### Features

- Snap-on type Rigid strap with two holes
- Greater load bearing capability
- Easy to install

### Applications

- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

### Standard Material

- Steel

### Standard Finish

- Zinc plated

### Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014