

Rigid Straps

Snap-On Type - Two Hole - Steel

Features

- Snap-on type Rigid strap with two holes
- Greater load bearing capability
- Easy to install

Applications

- Indoor or outdoor use
- Use to secure EMT, Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material


- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
541	15150	1/2"	50	500	9	2.43	.625
542	15160	3/4"	50	500	12	2.81	.685
543	15170	1"	25	250	9	3.28	.75
544	15180	1-1/4"	20	200	16	4.02	.875
545	15190	1-1/2"	10	100	14	4.58	1
546	15200	2"	---	50	5	5.22	1
527*	15010	2-1/2"	---	25	4	5.91	1
528*	15020	3"	---	25	5	6.71	1
529*	15030	3-1/2"	---	25	7	7.51	1
530*	15040	4"	---	25	7	8.31	1
530A	15042	5"	---	10	16	10.60	1.25
530B	15044	6"	---	10	7	11.85	1.25

*EMT and Rigid