


Rigid Straps

Snap-On Type - One Hole - Steel




Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
531A**	15041	1/4"	100	1000	14	1.51	.562
531B**	15045	3/8"	100	1000	12	1.81	.562
531	15050	1/2"	50	500	17	1.91	.625
532	15060	3/4"	50	500	25	2.21	.75
533	15070	1"	25	250	18	2.57	.875
534	15080	1-1/4"	20	200	18	2.79	.88
535	15090	1-1/2"	20	200	31	3.69	.899
536	15100	2"	10	100	24	4.17	1.14
517*	15670	2-1/2"	---	50	21	5	1.28
518*	15680	3"	---	25	12	5.55	1.28
519*	15690	3-1/2"	---	25	17	6.37	1.28
520*	15700	4"	---	25	17	6.87	1.28
520A**	15702	5"	---	10	17	9	1.50
520B**	15704	6"	---	10	20	10.35	1.50

*EMT and Rigid

**Not UL Listed

Snap-On Type - Two Hole - Steel



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	B
541	15150	1/2"	50	500	9	2.43	.625
542	15160	3/4"	50	500	12	2.81	.685
543	15170	1"	25	250	9	3.28	.75
544	15180	1-1/4"	20	200	16	4.02	.875
545	15190	1-1/2"	10	100	14	4.58	1
546	15200	2"	---	50	5	5.22	1
527*	15010	2-1/2"	---	25	4	5.87	1.43
528*	15020	3"	---	25	5	6.50	1.75
529*	15030	3-1/2"	---	25	7	7.12	2
530*	15040	4"	---	25	7	7.75	2.25
530A	15042	5"	---	10	16	10.60	1.25
530B	15044	6"	---	10	7	11.85	1.25

* EMT and Rigid

Features

- Snap-on type Rigid strap with one hole
- Inverted rib for strength
- Easy to install

Applications

- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014

Features

- Snap-on type Rigid strap with two holes
- Greater load bearing capability
- Easy to install

Applications

- Indoor or outdoor use
- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

Standard Material

- Steel

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB1-2014