


EMT ELBOWS

90° - GALVANIZED STEEL



FEATURES

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

APPLICATIONS

- For a secure connection to EMT conduit; bend enables directional changes in conduit

STANDARD MATERIAL


- Galvanized steel

CERTIFICATIONS

- UL Standard: UL 797
- Fed. Spec: WW-C-563
- NEMA: ANSI C80.3-2015

PART #	SIZE	INNER QTY.	SHIP CASE	WEIGHT/ CASE (LBS.)	(A) MIN. UL RADIUS	(B)STRAIGHT LEG EACH END	(C) OFFSET
81	1/2"	---	50	14	4"	2.875"	6.343"
82	3/4"	---	50	23	4.50"	2.875"	6.781"
83	1"	---	20	16	5.75"	3"	8.901"
84	1-1/4"	---	20	30	7.25"	3.25"	10.25"
85	1-1/2"	---	10	20	8.25"	3.625"	11.937"
86	2"	---	10	30	9.50"	4.1875"	14.031"
87	2-1/2"	1	50	300	10.50"	5.25"	16"
88	3"	1	35	315	13"	5.8125"	18.947"
89	3-1/2"	1	35	385	15"	6.75"	22.218"
89A	4"	1	25	375	16"	6.9375"	23.437"

60° - GALVANIZED STEEL



FEATURES

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

APPLICATIONS

- For a secure connection to EMT conduit; bend enables directional changes in conduit

STANDARD MATERIAL

- Galvanized steel

CERTIFICATIONS

- UL Standard: UL 797
- Fed. Spec: WW-C-563
- NEMA: ANSI C80.3-2015

PART #	SIZE	MASTER QTY.	WEIGHT/ CASE (LBS.)	(A) MIN. UL RADIUS	(B)STRAIGHT LEG EACH END
ELE-5060	1/2"	50	10	4"	2"
ELE-7560	3/4"	50	17	4-1/2"	2"
ELE-10060	1"	25	15	5-3/4"	2"
ELE-12560	1-1/4"	20	22	7-1/4"	2.69"
ELE-15060	1-1/2"	15	22	8-1/4"	3.25"
ELE-20060	2"	10	23	9-1/2"	4.25"
ELE-25060	2-1/2"	1	4	10-1/2"	5.25"
ELE-30060	3"	1	5	13"	5.81"
ELE-35060	3-1/2"	1	8	15"	6.75"
ELE-40060	4"	1	10	16"	6.94"