


# Rigid Couplings

## Three Piece Type - Steel



### Features

- For threaded Rigid or IMC conduit

### Applications

- Use as a threaded coupling between lengths of threaded Rigid or IMC conduit

### Standard Material


- Steel

### Standard Finish

- Zinc plated

| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | A    | B    |
|----------------|-------|---------------|-------------|-----------|-------------|------|------|
| <b>851S</b>    | 18631 | <b>1/2"</b>   | 20          | 200       | 20          | 1.43 | 1.36 |
| <b>852S</b>    | 18641 | <b>3/4"</b>   | 10          | 100       | 30          | 1.63 | 1.58 |
| <b>853S</b>    | 18651 | <b>1"</b>     | 5           | 50        | 46          | 1.81 | 1.89 |
| <b>854S</b>    | 18661 | <b>1-1/4"</b> | 5           | 50        | 110         | 2.19 | 2.38 |
| <b>855S</b>    | 18671 | <b>1-1/2"</b> | 3           | 30        | 147         | 2.31 | 2.83 |
| <b>856S</b>    | 18681 | <b>2"</b>     | ---         | 20        | 220         | 2.44 | 3.29 |

## Slip-On Type - Malleable Iron



### Features

- Slip on type
- Neoprene gasket ensures concrete tight seal
- Suitable for use in Class 1, Division 2 areas

### Applications

- Use to provide a quick and simple method of joining two pieces of threaded Rigid or IMC conduit when neither can be rotated

### Standard Material

- Malleable iron
- Neoprene gasket

| Catalog Number | UPC   | Size          | Unit Carton | Ship Case | Weight/Case | A    | B    |
|----------------|-------|---------------|-------------|-----------|-------------|------|------|
| <b>76</b>      | 70400 | <b>2"</b>     | 5           | 25        | 26          | 1.95 | 3.35 |
| <b>77</b>      | 70410 | <b>2-1/2"</b> | 2           | 10        | 23          | 3.25 | 4.75 |
| <b>78</b>      | 70420 | <b>3"</b>     | 2           | 10        | 30          | 3.25 | 5.50 |
| <b>79</b>      | 70430 | <b>3-1/2"</b> | 1           | 5         | 19          | 3.25 | 5.75 |
| <b>80</b>      | 70440 | <b>4"</b>     | 1           | 5         | 20          | 3.40 | 6.25 |