
# **EMT CONDUIT BODIES**

### **SET SCREW T TYPE**







### **FEATURES**

- Set screw T type
- Suitable for use in concrete

### **APPLICATIONS**

 Provides access to conductors for pulling, splicing and maintenance

### STANDARD MATERIAL

- Copper free aluminum die cast
- Steel screws

### STANDARD FINISH

Powder coat

### **CERTIFICATIONS**


- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA FB 1

PART #	SIZE	WIRE MAX. NUMBER	SIZE MAX. SIZE	INNER QTY.	MASTER QTY.	WEIGHT/ CASE (LBS.)	A	В	С
ET1	1/2"	1	6 AWG	10	100	32	4.72"	1.37"	2.03"
ET2	3/4"	2	6 AWG	10	50	30	5.57"	1.625"	2.335"
ET3	1"	3	6 AWG	5	25	15	6.46"	1.90"	2.705"
ET4	1-1/4"	3	2 AWG	2	10	17	8.528"	2.77"	3.63"
ET5	1-1/2"	3	2 AWG	2	10	19	8.528"	2.77"	3.63"
ET6	2"	3	2/0 AWG		2	5	10.831"	3.335"	3.98"
ET7	2-1/2"	3	4/0 AWG		1	7	13.50"	4.06"	5.825"
ET8	3"	3	250 MCM		1	7	13.50"	4.685"	5.825"
ET9	3-1/2"	3	350 MCM		1	9	15.937"	5.45"	7.06"
ET10	4"	4	350 MCM		1	9	15.937"	5.45"	7.06"

# EMT CONDUIT BODIES WITH COVER AND GASKET

## SET SCREW LB TYPE







### **FEATURES**

- Set screw LB type with cover and gasket
- Suitable for use in concrete

### **APPLICATIONS**

 Provides access to conductors for pulling, splicing and maintenance

### STANDARD MATERIAL

- Copper free aluminum die cast
- Steel screws
- Cover Stamped steel
- Gasket Neoprene rubber

### STANDARD FINISH

Powder coat

### **CERTIFICATIONS**

- UL Standard: 514A
- Fed. Spec. W-C-586D
- NEMA FB 1

PART #	SIZE	WIRE:	SIZE MAX. SIZE	INNER QTY.	MASTER QTY.	WEIGHT/ CASE (LBS.)	А	В	C
ELB1CG	1/2"	1	6 AWG	10	100	32	4.295"	2.15"	1.33"
ELB2CG	3/4"	2	6 AWG	10	50	23	5.09"	2.43"	1.54"
ELB3CG	1"	3	6 AWG	5	25	19	5.915"	2.765"	1.74"
ELB4CG	1-1/4"	3	2 AWG	2	10	14	7.894"	3.665"	2.49"
ELB5CG	1-1/2"	3	2 AWG	2	10	15	7.894"	3.665"	2.49"
ELB6CG	2"	3	2/0 AWG	1	5	14	10.134"	4.275"	3.10"
ELB7CG	2-1/2"	3	2/0 AWG		1	7	12.50"	5.437"	4.45"
ELB8CG	3"	3	4/0 AWG		1	7	12.50"	5.657"	4.45"
ELB9CG	3-1/2"	3	400 MCM		1	10	15.50"	6.922"	5.50"
ELB10CG	4"	3	400 MCM		1	10	15.50"	6.922 "	5.50"